NBSIR 78-1499



An Evaluation of Existing Models Describing the Migration of Additives in Polymers

I. C. Sanchez, S. S. Chang, F. L. McCrackin and L. E. Smith

Polymer Science & Standards Division Center for Material Science National Bureau of Standards Washington, D.C. 20234

Semi-annual Report for Period September 1, 1977 - March 30, 1978

Issued July 1978


Prepared for

Bureau of Foods

Food and Drug Administration

Washington, D.C. 20201

Interagency Reimbursable Agreement



		į

5 (_ 1013

NBSIR 78-1499

AN EVALUATION OF EXISTING MODELS DESCRIBING THE MIGRATION OF ADDITIVES IN POLYMERS

I. C. Sanchez, S. S. Chang, F. L. McCrackin and L. E. Smith

Polymer Science & Standards Division Center for Material Science National Bureau of Standards Washington, D.C. 20234

Semi-annual Report for Period September 1, 1977 - March 30, 1978

Issued July 1978

Prepared for
Bureau of Foods
Food and Drug Administration
Washington, D.C. 20201
Interagency Reimbursable Agreement



NBS Late year, Real, 18 18 11.

U.S. DEPARTMENT OF COMMERCE, Juanita M. Kreps, Secretary

Dr. Sidney Harman, Under Secretary

Jordan J. Baruch, Assistant Secretary for Science and Technology NATIONAL BUREAU OF STANDARDS, Ernest Ambier, Director



AN EVALUATION OF EXISTING MODELS DESCRIBING THE MIGRATION OF ADDITIVES IN POLYMERS

I. C. Sanchez

S. S. Chang

F. L. McCrackin

L. E. Smith

Report to: Bureau of Foods
Food and Drug Administration

Covering the period September 1, 1977

to

March 30, 1978



SUMMARY

The objective of this work is the development of mathematical models that describe the migration of a variety of small molecules in polymers that have applications in food contact uses. In the most general cases, these models will be able to predict the amount of additive migration given any particular time and temperature history. These models can serve as the technical basis for more efficient regulatory methods under existing frameworks or in the design and implementation of new indirect additive regulations or policy.

The existing data on additive migration applicable to food contact uses have been surveyed and organized for reference. Existing models describing additive migration into foodsimulating solvents have been surveyed and evaluated. From these considerations four main conclusions can be drawn:

- 1) At a given temperature above the glass transition of the polymer, diffusion in the polymer is invariably proportional to the concentration gradient of the diffusing species. The concentration gradient is the rate of change in concentration with distance in the polymer.
- 2) Diffusion in polymers below their glass transition is complex and difficult to generalize.
- 3) Above the glass transition temperature, the temperature dependence of diffusion is primarily determined by the properties of the polymer and relatively independent of the size and shape of the diffusant.
- 4) The temperature dependence of the diffusion is strong and non-Arrhenius. This means that a plot of the logarithum of the diffusion constant versus the inverse of the absolute temperature will generally be non-linear.

To model migration of minor constituents from a polymeric film to a food simulating solvent requires knowledge of (1) the equilibrium distribution of a migrant between polymer and solvent phases, i.e., the distribution or partition coefficient K and (2) the diffusion coefficient D of the migrant in the polymer. This is the minimum amount of information required to describe polymer/migrant/solvent system. For a polymer at a temperature above its glass transition temperature, knowledge of K and D allows one to calculate migration as a function of time and as a function of temperature if the temperature variation of K and D are also known.

We have shown that the distribution coefficient is related to the migrants' chemical potential in the polymer and solvent and have demonstrated how K and its temperature dependence can be calculated using recently developed theories of the chemical potential. Our preliminary calculations have been very encouraging. Additionally, K is amenable to experimental determination by utilization of gas chromatographic techniques.

Existing theories of the diffusion coefficient can be characterized as being correlative rather than predictive. We have formulated a new theory for D which promises to be more predictive than existing theories. This new theory is based on the thermodynamic theory of fluctuations and depends on: (1) the shape and size of the diffusant, (2) the polymer-diffusant intermolecular interactions, and (3) the isothermal compressibility of the polymer.

TABLE OF CONTENTS

	Page
INTRODUCTION	. 7
SURVEY OF MIGRATION DATA APPLICABLE TO FOOD-CONTACT USES	. 3
Introduction	
Literature References	. 33
Introduction	. 42
PRELIMINARY CLASSIFICATION OF ADDITIVE TYPES	. 55



INTRODUCTION

The effective regulation of indirect food additives arising from the migration of substances from plastic packaging materials involves three main technical questions:

- 1) What substances are present in the packaging material that can migrate into foods?
- 2) To what extent and at what rate can these substances be reasonably expected to migrate into the food?
- 3) What are the physiologic consequences of the ingestion of these quantities of these substances by the public?

The first of these questions can generally be answered by consideration of the synthesis and fabrication steps of the packaging material supported by straightforward analytical methods. The third question is a complex toxicological problem which at present can only be answered with case by case testing and even then is subject to considerable debate. The second question, however, is a measurement problem capable of general resolution and is the subject of this FDA-sponsored work.

The objective of this work is the development of mathematical models that describe the migration of a variety of small molecules in polymers that have applications in food contact uses. In the most general cases, these models will be able to predict the amount of additive migration given any particular time and temperature history. The models will be designed to require a minimum of laboratory data determined for the particular polymer-migrant system.

These models will serve several purposes. They can serve as a basis for the classification of polymers and additives into groups with similar migration behavior for regulatory purposes. They can reduce or eliminate the need for extensive extraction data to qualify new polymer-additive systems for food contact uses. For example, a change in a packaging process

requiring a higher filling temperature could be considered on the basis of an extrapolation from existing data without the need for additional laboratory work.

Physical models of migration can allow a relatively rapid estimate of maximum exposure of the public to any given additive or additive type. These estimates can guide public policy and provide a quantitative basis for toxicological assessments of risk. Finally, physical models or description of migration behavior can provide the technical information for a comprehensive review or adjustment of the total regulatory framework covering indirect food additives.

The first steps in the development and assessment of such models are given in this report. The first section presents a preliminary survey of migration data applicable to food contact situations that are available in the current literature. The second section surveys available models describing migration and evaluates their present and potential utility.

INTRODUCTION

The following literature survey collects and organizes available data on migration rates of low molecular weight species from polymeric matrices that have primary applicability to food contact situations. Only data that apply to food contact situations have been included. References that are useful in formulating and testing general models of migration will be added as the need arises. References prior to 1970 are also not explicitly included as these papers are adequately referenced in the cited, later work.

The ordered index is sorted first by type of polymer, then by the nature of the migrating species, and then by solvent. The abbreviations used are explained in the following section. The remarks primarily refer to the type of data presented and the time and temperature interval for which data are available.

KEY TO ABBREVIATIONS

* ******POL YMERS*****

ACRYLCNITRILE/EUTADIENE/STYRENE ARS ABS/MA ABS/MA/MMA COPOLYMER CA CELLULOSE ACETATE EIP ETHYLENE/PROPYLENE E/PHAC ETHYLENE/PHENYL ACETATE E/VAC ETHYLENE/VINYL ACETATE EPCXY RESIN EPXR F-0 FLUORCPCLYMEKS MFR MELAMINE FORMALDEHYDE RESIN N6 NYLON 6 NR NATURAL RUBBER PA PCLYAMIDES PAN POLYACRYLONITRILE PAT POLYACETAL PBD PCLYBUTADIENE PUMS PULYDIMETHYLSILGXANE PE POLYETHYLENE PES POLYESTER PMA POLYMETHACRYLATE PMMA PCLY (METHYL METHACRYLATE) PMP POLY (4-METHYLPENTENE-1) POM POLYOXYMETHYLENE PCLYPRCPYLENE 99 PPHAC POLYPHENYL ACETATE PR PHENOLIC RESIN MS POLYSTYRENE PU PCLYURETHANE POYL (VINLY CHLCRIDE) PVC PVC/ABS POLY(VINYL CHLORIDE)/ABS POLY(VINYLIDENE CHLORIDE) PVDC SAN STYRENE/ACRYLUNITRILE

SR SILICONE RUBBER

V/APB VINYL ACETATE/VINYL PYRROLIDONE/VINYL BUTYL ETHER

* ******MIGKANTS*****

SBR

ABC ACETYL TRIBUTYL CITRATE

ACA AMINOCROTONIC ACID ESTERS

AHA 1-AMINO-4-HYDROXYANTHRAQUINONE

AN ACRYLONITRILE

BDO BUTADIENE CLIGOMER

STYRENE/BUTADIENE RUBBER

BHA TERT-BUTYL-4-HYDROXYANISOLE

BHT 2.6-DI-TERT-BUTYL-P-CRESCL; IONUL; ADVASTAB 401 BPBG BUTYL PHTHALYL BUTYLGLYCOLATE BPD BENZOPHENDNE DEFIVATIVES: DASTIB-244.-256,-28) HST BUTYL STEARATE BTA BENZOTRIAZCLE-PHENOLS; TINUVIN P; TINUVIN 320 BTAC CHLOROBENZUTRIAZOLE-PHENOLS; TINUVIN 326; TINUVIN 327 CAST CALCIUM STEARATE CU CADMIUN PIGMENTS OBP DIBUTYL PHTHALATE DBS DIBUTYL SEBACATE DIBUTYL TIN CEMPOUNDS DBSN DCDA DICYANCIAMIDE DHA 1,4-DIHYDROXYANTHRAQUINCNE DHBP 2.4-DIFYDROXYBENZOPHENONE DNP DINCNYL PHTHALATE UOP DIOCTYL PHTHALATE DIDCTYL TIN COMPOUNDS DOSN UTCT N-DOTR IACOTANE OTP DIDODECYL-3,3'-THICPROPIONATE HCHO FCRMALCEHYDE HEBP 2-HYDROXY-4-(2'-ETHYLHEXYL)-OXYBENZOPHENONE; DASTIB 242 2-HYDROXY-4-METHOXYBENZOPHENONE; UV ABSORRER MOB: ADVASTAB 45 HMBP HOBP 2-HYDROXY-4-DCTOXYBENZOPHENDNE: ADVASTAB 46: CYASORS UV531 HXD N-HEXADECANE MGST MAGNESIUM STEARATE MMA METHYL METHACRYLATE MMBP 2.2 - METHYLENE-BIS-(4-METHYL-6-TERT-BUTYLPHENOL); 2246 MSN METHYL TIN COMPCUNDS MICREWAX MW NAAB 4-NITRC-4"-AMINOAZOBENZENE ODE N-OCTADECYL-DIETHANULAMINE N-OCTADECYL-B-(4"-HYDROXY-3,5"-DI-T-6UTYLPHENYL)PROPIONATE DHBP PAP PCLYADIPATE PB LEAD PH PHENUL RP ALKYL PHTHALATES RSE ALKYL SULFONIC ACID ESTERS STYRENE 5 STEARIC ACID AMIDE SA SN TIN CEMPCUNDS STP DISTEARYL THICDIPROPIONATE: ADVASTAB PS802: ANTIOXYDANS AS 4.4°-THIO-BIS-(6-T-BUTYL-M-CRESOL); ADVASTAB 415; SANTONOX THC TCP TRICRESGL PHOSPHATE TEP TRIETHYL PHOSPHATE TRIGLYCERIDES TG TIUZ TITANIUM DICXIDL TNPP TRIS-(NCNYLPHENYL) PHCSPHATE; ADVASTAB TNPP TTB 1.3.5-TRIMETHYL-2.4.6-TRIS(3.5-DI-T-BUTYL-4-HYDROXYBENZYL) VAC VINYL ACETATE V.C. VINYL CHLORIDE PARAFFIN WAX WAX XYZ BENZENE; CHLORGHENZENE; ETHYLENE GLYCOL; ETHYL EHTER; ETHANOL; N-ALKANE ZINC STEARATE ZNST

* ****** SOL VENT S** ***

AQ AQUEOUS SCLUTIONS OF SALTS; DETERGENTS; ETC.

SL BLGOD

DP DAIRY PRODUCTS

ETOH ETHANCL

ET20 DIETHYL ETHER FHC FLUORCHYDROCARBON

HC HYDROCARBONS

H20 WATER

MEDH METHANOL
MF MEAT AND FAT

ME MEAT AND FAT NH N-FEPTANE

OIL: FAT AND SIMULANT

ROH ALCOHOLS R2O ETHERS

TG INDIVIDUAL TRIGLYCERIDES

VEG VEGETABLE

CA CHEMICAL ANALYSIS

COLOR CCLGRIMETRY

GC GAS CHROMATEGRAPHY

GM GRAVIMETRY
PHOTO PHOTOMETRY
POLAR PCLARCGRAPHY
RAD RADICANALYSIS

SECT SECTIONAL ANALYSIS

SPEC SPECTRESCOPY

TLC THIN LAYER CHRCMATORGRAPHY

******REMARKS****

AC ACTIVITY COEFFICIENT

APP APPARATUS/METHOD

CMT CORRELATION/MODEL/THEORY

CP CONCENTRATION GRADIENT PROFILE

D DIFFUSION CGEFFICIENT ENI EXTRACT NOT IDENTIFIED

GR GRAPHS

H* ACTIVATION ENERGY

K PARTITION COEFFICIENT
MC MIGRANT CONCENTRATION

NC NC COMPOSITION NKD NO KINETIC DATA

NS NC SURFACE AREA INFORMATION

NTT NC TEMPERATURE OR TIME INFORMATION

PARTS PER HUNDRED PARTS OF RESIN PHR

RCCM TEMPERATURE RT SURPTION-DESORPTION SD SECTIONAL CBSERVATION SECT

SCLUBILITY SOL

C-CELCIUS: D-DAY: H-HOUR; M-MONTH; W-WEEK: Y-YEAR UNITS

ORDERED INDEX TO AVAILABLE DATA

POL YMER	MIGRANT	SOLVENT	METHOD	REMARKS (DATA POINTS AT TEMPERATURE/TIME)	REFERENCE
ABS	ABC	ETCH		NKD: TO 80C/TO 50	124
ABS	ABC	H2C		NKD. TO 80C/TO 5D	124
ABS	AN	AQ		GR: RT/ TO 2000	144
ABS	AN	H20		GR: RT/ TO 2000	144
ABS	BST	ETOH		NKD. TO 89C/TO 5D	124
ABS	BST	H20		NKD, TO 80C/TO 50	124
ABS	S	AQ		GR: RT/ TO 200D	244
ABS	S	ETOH		NKD. TO 80C/TO 5D	124
ABS	S	H2C		NKD. TO 8JC/TO 5D	124
ABS	S	H20		GR: RT/ TO 200D	144
ABS	XYZ	5500		INTER-POLYMER, APP. 70C/TO 1320D	112
CA	DGP	ET20	GC	NKD. TO 98C/TO 13D	10
CA	DOP	HC	GC	NKD. TO 96C/TO 10D	10
CA	DOP	OIL	GC	NKD, TO 98C/TO 10D	13
CA	DOP	TG	GC	NKD, TO 98C/TO 10D	10
CA	XYZ			Q	100
E/P	HXD			_	141
EPXR	LC40	400	•	CMT .	. 99
FP MFR	HCHO	H20		NKD 0-90C/1-10D	122
	HCHB	H2C		D	141
NR NR	DTCT			•	. 19
NR NR	WAX		GM	TO 280D BLOOM	158
NR NR	XYZ		GM	D. CMT. SMEAR	140
PA	CD	ETOH		EJC/GH	190
PA	CD	ET20		8CC/6H	193
PA	CD	H2G		80C/6H	190
PA	CD	HOAC		80C/6H	. 190
PBD	HXD	NOAC.		D. CMT	139
PBD	HXD			D. CMT. SMEAR	145
PBU	HXD			D	141
PDMS	DTCT			D	141
PE	EHA.	ET20	GC	NKD, TO 98C/TO 12D	10
PE	EHA	HC HC	*GC	NKD. TO 98C/TO 10D	10
PE	EHA	OIL	GC	NKD, TO 98C/TO 10D	اً زُرُ
PE	EHA	TG	GC	NKD, TO 98C/TO 10D	1 2
PE	BPD	ETOH		45C/2.13D. 70C/2H. 100.121C/0.5H	168
PE	EPD	H20		45C/2.10D. 70C/2H. 130.121C/0.5H	168
PE	EPD	HOAC		45C/2.10D. 7UC/2H. 10U.121C/0.5H	168
PE	BPD	OIL		45C/2.10D, 7JC/2H, 100,121C/0.5H	168
PE	ETAC	ETCH	TLC	NKD. 45C/10D	170
PE	ETAC	нс	TLC	NKD, 45C/10D ·	170
PE	ETAC	HC		GR: 40-65C/TO 60D	118
PE	ETAC	H20	TLC	NKD. 45C/10D	. 170

```
PE
        STAC
                 HDAC
                         TLC
                                 NKD. 45C/10D
                                                                                             170 .
                         POLAR
                                 4.20-25C/1.2.3.6M. 45C/10D.6M
PF
        PTAC
                 OIL
                                                                                             166
PE
        PTAC
                 CIL
                          TLC
                                 NKD. 45C/10D
                                                                                             170
PΕ
                 CIL
                                 GR: 43-65C/TO 60D
        STAC
                                                                                             118
PE
        CD
                 ETOH
                                 8JC/6H
                                                                                             190
PE
                                 84C/6H
        CD
                 FT20
                                                                                             190
PE
        CD
                 H20
                                 8CC/6H
                                                                                             190
PF
        CD
                 HOAC
                                 83C/6H
                                                                                             190
PE
        DHBP
                 H2C
                          HAD
                                 CMT. D. 44-75C/TO 1000H
                                                                                             177
PF
        DCP
                                 INTER-POLYMER. APP. 70C/TO 1320D
                                                                                             112
PΕ
        DTP
                          RAD
                                 D. H*. CMT. SMEAR. 23-78C
                                                                                              73
PE
                 ETOH
                                 45C/2.13D, 70C/2H, 100.121C/0.5H
        HE8P
                                                                                             168
PE
                                 45C/2.1JD. 70C/2H. 103.121C/3.5H
        BEBP
                 HSC
                                                                                             168
PE
                 FOAC
                                 45C/2.10D. 70C/2H. 100.121C/0.5H
        HEBP
                                                                                             168
PĒ
        HEBP
                 OIL
                                 45C/2,10D, 7)C/2H, 100,121C/0.5H
                                                                                             168
PE
        HMBP
                 ETOH
                                 NKD. 45C/10D
                          TLC
                                                                                             170
PF
        HMBP
                 HC
                         TLC
                                 NKD. 45C/10D
                                                                                             170
PΕ
        HMBP
                 H2C
                         TLC
                                 NKD. 45C/10D
                                                                                             170
PE
        HMEP
                 HOAC
                          TLC
                                 NKD. 45C/10D
                                                                                             170
PΕ
        HMBP
                 OIL
                          TLC
                                 NKD. 45C/10D
                                                                                             170
PF
        HORP
                 ETOH
                                 45C/2.10D. 70C/2H. 100.121C/0.5H
                                                                                             168
PE
        HOBP
                          RAD
                                 D. H. SMEAR. EXTRACT 044C/TO 255D
                 h20
                                                                                             77
PE
        HCBP
                 H20
                                 45C/2+13D+ 79C/2H+ 1()+121C/0+5H
                                                                                             168
PF
        HCBP
                 HOAC
                                 45C/2,10D, 70C/2H, 100,121C/0.5H
                                                                                             168
PF
        FOSP
                 CIL
                                 45C/2.10D. 70C/2H. 100.121C/0.5H
                                                                                             168
PΕ
        MMBP
                          RAD
                                 D. K. INTER-POLYMER
                                                                                              13
PE
        ODE
                          RAD
                                                                                              73
                                 D. H*. CMT. SMEAR. 20-78C
PΕ
        SA
                 ET20
                         RAD
                                 20C/60D. 65C/5H. GR: 0.5-5H
                                                                                             132
PF
        SA
                 FHC
                          RAD
                                                                                              54
                                 20C/43.60D
PΕ
                                 4-25%DOP, APP, 20C/30,60D, 40C/10D, GR: TO 80C/TO 80D
        SA
                 HC
                         RAD
                                                                                             46
PE
        SA
                 HC
                          RAD
                                 20C/43,60D
                                                                                             54
PF
        SA
                          RAD
                                 20C/6CD. 65C/5H. GR: 0.5-5H
                 F.C
                                                                                             132
PE
        SA
                 MECH
                         RAD
                                 28C/60D, 65C/5H, GR: 3.5-5H
                                                                                             132
PΕ
        SA
                 CIL
                          RAD
                                 APP. 20C/6)D. 65C/5H. GR: TO 65C/TO 60D
                                                                                              39
PE
        SA
                 CIL
                          RAD
                                 20C/30.60D
                                                                                              45
                                 4-25%DOP, APP, 20C/30.60D, 40C/10D, GR: TO 60C/TO 86D
PΕ
        SA
                 OIL
                         RAD
                                                                                              40
PE
                 OIL
                         RAC
        SA
                                 65C/2.5H. GR: TO 6H
                                                                                              51
PE
                 CIL
                                 200/30.6JD. GR: TO 60D
        SA
                         FLAD
                                                                                              52
PE
        SA
                 CIL
                          RAD
                                 APP, FAT-PENETRATION, 200/30.600, 650/2.5H
                                                                                              53
PE
                 OIL
        SA
                         RAD
                                 20C/43.60D
                                                                                              54
                                 20C/60D, 65C/5H, GR: 0.5-5H
PF
                 CIL
                         RAD
                                                                                             132
        SA
PE
        SA
                 R2C
                         RAD
                                 4-25%DOP. APP. 20C/30.60D. 40C/10D. GR: TO 80C/TO 80D
                                                                                              46
PE
                 R20
                         RAD
                                 20C/43.60D
                                                                                              54
        SA
PE
        SA
                 TG
                          RAD
                                 65.83C/2.5H
                                                                                              38
PE
        SA
                 TG
                          RAD
                                 2JC/3J.60D
                                                                                              45
PF
        SA
                 TG
                         RAD
                                 65C/2.5H. GR: TO 6H
                                                                                              51
PC
        SA
                 TG
                         RAD
                                 20C/30.60D. GR: TO 60D
                                                                                              52
PE
        SA
                 TG
                         KAD
                                 APP. FAT-PENETRATION: 20C/30:60D: 65C/2:5H
PE
        SA
                                 SURFACE
                                                                                              5)
PE
                 ET20
                          RAD
                                 20C/69D. 65C/5H. GR: 0.5-5H
                                                                                             132
        TTB
PE
                         RAD
                                                                                              54
        TTB
                 FHC
                                 2JC/43.60D
                                 4-25%00P. APP. 26C/30.60D. 40C/10D. GR: TO 80C/TO 80D
PE
        TTB
                 HC
                          RAD
                                                                                             46
PE
        TTB
                 ЬC
                          CAR
                                 200/43.600
                                                                                              54
PE'
                 HС
                          RAD
                                 20C/6JD. 65C/5H. GR: 0.5-5H
                                                                                             132
        TTB
                                                                                             132
PE
        TTB
                 MECH
                          RAD
                                 26C/6JD. 65C/5H. GR: 0.5-5H
                                                                                              39
PE
        TTB
                 OIL
                          RAD
                                 APP, 200/6,D, 650/5H, GR: TO 650/TO 60D
                                                                                              45
PE
        TTB
                 CIL
                          RAD
                                 26C/33.60D
```

PE

TTB

OIL

RAD

4-25%DOP. APP. 20C/30.60D. 40C/10D. GR: TO 83C/TO 83D

46

```
PE
        YTB
                 CIL
                          RAD
                                 65C/2.5H, GR: TO 6H
                                                                                               51
                                                                                               52 '
                                 200/30,600, GR: TO 600
PE
        TTB
                 OIL
                          RAD
                                 APP, FAT-PENETRATION, 20C/30.60D, 65C/2.5H
PE
        TTB
                 CIL
                          RAD
                                                                                               53
                 CIL
                          RAD
                                 20C/43,60D
                                                                                               54
PE
        TTB
                                 24C/64D, 65C/5H, GR: 3.5-5H
PE
        TIB
                 CIL
                          RAD
                                                                                              132
                 R20
                                 4-25%DOP. APP. 20C/30.60D, 40C/10D. GR: TO 80C/TO 80D
                          RAD
PF
        TTB
                                                                                               46
PE
        TTB
                 R2C
                          RAD
                                 20C/43,60D
                                                                                               54
                                 65,83C/2,5H
PE
        TTB
                 TG
                          RAD
                                                                                               38
                 TG
                          RAD
                                 200/30,600
                                                                                               45
PE
        TTB
                 TG
                          KAD
                                 65C/2.5H, GR: TO 6H
                                                                                               51
PE
        TTB
                 TG
                          RAD
                                 20C/30.60D. GR: TO 60D
                                                                                               52
PE
        TTB
PE
        TTB
                 TG
                          RAD
                                 APP. FAT-PENETRATION. 20C/30.60D. 65C/2.5H
                                                                                               53
                                 TO 50C/TO 8W
PE
         XYZ
                 H20
                                                                                              119
PE
                                                                                               65
PE
                          RAD
                                 D. H=, CMT, SMEAR, 20-78C
                                                                                               73
                 OIL
                                 FAT-MIGRATION
                                                                                               96
PE
PMA
         CBP
                 ETOH
                          POLAR
                                 NKD: 45C/10D
                                                                                              189
PMA
        DEP
                 HC
                          POLAR
                                 NKD: 45C/10D
                                                                                              189
PMA
        CBP
                 h20
                          POLAR
                                 NKD, 45C/10D
                                                                                              189
                          POLAR
                                 NKD, 45C/10D
                                                                                              189
PMA
        DBP
                 HOAC
                 ETOH
                          PCLAR NKD. 45C/100
                                                                                              189
PMA
        DOP
                 HC
                          POLAR NKD. 45C/10D
                                                                                              189
PMA
        DOP
                          POLAR NKD, 45C/10D
                                                                                              189
PMA
        DOP
                 H20
                          POLAR
                                 NKD' 45C/10D
                                                                                              189
PMA
        DOP
                 HDAC
PMMA
        HMBP
                 ETCH
                          TLC
                                 NKD, 45C/10D
                                                                                              170
                                 NKD, 45C/10D
                                                                                              170
PMMA
        HMRP
                 HC
                          TLC
                                 NKD. 45C/10D
                                                                                              170
PMMA
        HMBP
                 H20
                          TLC
        HMBP
                 FOAC
                          TLC
                                 NKD. 45C/10D
                                                                                              170
PMMA
        HMBP
                 OIL
                          TLC
                                 NKD. 45C/10D
                                                                                              170
PMMA
PMMA
        AMM
                 H20
                                 CMT, GR: 37-90C/10H
                                                                                              162
         XYZ
                                                                                              100
PMMA
PMP
        DTP
                          RAD
                                 D. H*, CMT, SMEAR, 20-78C
                                                                                               73
PMP
                          RAD
                                 D. H. CMT. SMEAR. 20-78C
                                                                                               73
                                                                                               97
POM
        DCDA
                 H20
                          PHOTO
                                  37C/1,3,5,7D, 100C/2H, GR: TO 10D
                                  37C/1.3.5.7D. 100C/2H. GR: TO 10D
                                                                                               97
POM
        HCHO
                 1.20
                          PHCTO
POM
        NNBP
                 H20
                          PHOTO
                                  37C/1.3.5.7D, 100C/2H, GR: TO 10D
                                                                                               97
PP
         EHT
                                  NKD. 45C/10D
                                                                                              167
PP
         ETAC
                 HC
                                  GR: 40-65C/TO 60D
                                                                                              118
PP
         ETAC
                 OIL
                                  GR: 40-65C/TO 60D
                                                                                              118
PP
         DHBP
                 H20
                          RAD
                                  CMT. D. 44-75C/TO 1000H
                                                                                              177
PP
         DTP
                          RAD
                                 C. H*, CMT, SMEAR, 20-78C
                                                                                               73
                                  45C/2.13D. 70C/2H. 100.121C/0.5H
PP
        HOBP
                 ETOH
                                                                                              168
PP
                                  45C/2,10D, 70C/2H, 103,121C/9.5H
                                                                                              165
         HOBP
                 H20
                                  45C/2.10D. 7JC/2H. 10J.121C/0.5H
PP
                                                                                              168
        HOBP
                 HOAC
                                  45C/2.1JD, 70C/2H, 100.121C/0.5H
PP
                                                                                              168
         HOSP
                 CIL
                                                                                               73
PP
                                 D. H#. CMT. SMEAR. 20-78C
         ODE
                          RAD
                                  GR: 40-650/TO 600
                                                                                              118
00
         CHBP
                 HC
PP
         OHBP
                 CIL
                                  GR: 49-65C/TO 60D
                                                                                              118
PP
                                 D. HA. CMT. SMEAR. 20-78C
                                                                                               73
                          RAD
PR
        HCHO
                                          20-80C
                                                                                              165
                                 NC.
PR
         PH
                                  NC .
                                          20-80C
                                                                                              165
                                  NKD. TO 98C/TD. 10D
PS
         CHT
                 ET20
                          GÇ
                                                                                               10
PS
                                  NKD. TO 98C/TO 10D
                                                                                               10
         BET
                 hC
                          GC
PS
         EHT
                 CIL
                          GC
                                  NKD, TO 98C/TO 100
                                                                                               25
PS
         BHT
                 TG
                          GC
                                  NKD. TO 98C/TO 10D
                                                                                               23
PS
         EhT
                                  NKD. 45C/10D
                                                                                              167
                          RAD
                                                                                              132
PS
         EST
                 ET20
                                  20C/60D, 65C/5H, GR: 0.5-5H
PS
         BST
                 FHC
                          RAD
                                  20C/43,60D
```

```
PS
                                                                                           46
        PST
                HC
                         FAD
                                4-25%DDP, APP, 200/30,60D, 400/10D, GR: TO 800/TO 80D
PS
        EST
                HC
                         RAD
                                230/43,630
                                                                                           54
                                200/60D, 650/5H, GR: 0.5-5H
PS
        PST
                HC
                         RAD
                                                                                          132
PS
        BST
                H2C
                                GR: 6)C/TO 1Y
                                                                                          123
PS
        PST
                MECH
                         RAD
                                20C/60D, 65C/5H, GR: 0.5-5H
                                                                                          132
PS
        BST
                CIL
                        RAD
                                APP, 20C/6JD, 65C/5H, GR: TO 65C/TO 60D
                                                                                           39
PS
        BST
                GIL
                        RAD
                                20C/30.60D
                                                                                           45
PS
        BST
                OIL
                        RAD
                                4-25%DOP, APP, 200/30,600, 400/100, GR: TO 600/TO 800
                                                                                           45
PS
        8ST
                                65C/2.5H. GR: TO 6H
                CIL
                        FAD
                                                                                           51
PS
        BST
                CIL
                        RAD
                                20C/30,60D, GR: TO 60D
                                                                                           52
25
        BST
                                APP. FAT-PENETRATION, 20C/30,600, 65C/2,5H
                                                                                           53
                CIL
                        FAD
PS
        BST
                CIL
                                20C/43,60D
                        RAD
                                                                                           54
PS
        est
                CIL
                        RAD
                                20C/69D. 65C/5H. GR: 0.5-5H
                                                                                          132
PS
        BST
                R20
                        RAD
                                4-25%DOP, APP, 20C/30.60D, 40C/10D, GR: TO 80C/TO 80D
                                                                                           46
PS
        PST
                R2C
                        RAD
                                20C/43,60D
                                                                                           54
PS
        est
                TG
                        RAD
                                65,83C/2,5H
                                                                                           38
PS
                TG
                        RAD
                                                                                           45
        BST
                                20C/30.60D
PS
        BST
                TG
                        RAD
                                65C/2.5H. GR: TO 6H
                                                                                           51
PS
        BST
                TG
                        FAD
                                200/30,60D, GR: TO 60D
PS
        BST
                TG
                         RAD
                                APP. FAT-PENETRATION, 200/30,600, 650/2,5H
                                                                                           53
PS
        BST
                                CMT. D. 20.40.60C/133D. GR: 13-193D
                                                                                          174
        CD
                                                                                          190
PS
                ETCH
                                80C/6H
                                80C/6H
                                                                                          190
PS
        CD
                ET20
PS
        CD
                h2C
                                80C/6H
                                                                                          190
PS
        CD
                HOAC
                                80C/6H
                                                                                          19)
PS
        UGP
                ETCH
                                NKD. TO 800/TO 50
                                                                                          124
PS
        DOP
                H2C
                                NKD. TO BUC/TO 5D
                                                                                          124
PS
        HMBP
                ETCH
                         TLC
                                NKD. 45C/13D
                                                                                          17)
                                NKD, 45C/10D
PS
        HMBP
                FC
                         TLC
                                                                                          17.0
                                NKC. 45C/10D
                                                                                          170
PS
        HMBP
                H2C
                         TLC
PS
        HMBP
                FOAC
                         TLC
                                NKD. 45C/10D
                                                                                         170
PS
                                NKD. 45C/10D
                                                                                          173
        HMBP
                CIL
                         TLC
PS
                ETCH
                                45C/2,10D, 70C/2H, 100,121C/0.5H
        HOBP
                                                                                          168
PS
                H2C
                                45C/2.1vD, 70C/2H, 100.121C/0.5H
                                                                                         169
        HOBP
PS
                                45C/2.10D. 70C/2H. 100.121C/0.5H
        HOBP
                HOAC
                                                                                          1.68
PS
                                45C/2,10D, 70C/2H, 130,121C/0.5H
                                                                                          168
        HOBP
                GIL
                                                                                         140
PS
                                D. CMT. SMEAR
        HXD
PS
        PAP
                                INTER-POLYMER, APP, 70C/TO 1320D
                                                                                          112
PS
        S
                AΩ
                                NTT, 1,3,5D
                                                                                          126
PS
                DP
                                CMT. D. GR: TO 20C/TO 30D
                                                                                          29
                         GC
        S
25
                ETOH
                                GR: 23-70C/0.01-720D
                                                                                          131
        S
                                                                                          29
PS
        S
                H2C
                                CMT. D. GR: TO 20C/TO 30D
                                                                                         126
PS
        S
                H2C
                                NTT, 1,3,5D
PS
        S
                H2C
                                GR: 60C/TO 1Y
                                                                                          128
PS
        S
                H2C
                                GR: 23-70C/3.01-720D
                                                                                          131
        S
                                CMT, GR: 37-90C/10H
                                                                                          162
PS
                H2G
                                NTT, 1,3,5D
                                                                                          126
PS
        S
                HCAC
                                                                                          131
PS
        S
                HOAC
                                GR: 23-7(C/0.01-720D
                                                                                          126
PS
        S
                OIL
                                NTT. 1.3.5D
                                                                                          131
PS
        S
                                GR: 23-70C/0.01-720D
                 OIL
                                                                                          174
PS
                                CMT. D. 25.45.60C/100D. GR: 10-100D
        S
                                                                                          167
PS
        STP
                                NKD. 45C/1JD
                                                                                          167
PS
        TBC
                                NKD. 45C/130
                                                                                          167
PS
        TNPP
                                NKD. 45C/IJD
                                                                                          132
                                20C/6JD, 65C/5H, GR: 0.5-5H
PS
        TTB
                ET20
                       RAD
                                                                                           54
                FHC
PS
        TTB
                         RAD
                                20C/43.63D
                                4-25%DGP, APP, 20C/30,60D, 40C/10D, GR: TO 80C/TO 80D
                                                                                           46
PS
        TTE
                 HC
                         F. AU
                                                                                           54
PS
        TTB
                         RAD
                                2JC/43,60D
                HC
```

```
PS
        TTB
                         RAD
                                20C/60D, 65C/5H, GR: 0.5-5H
                 HC
                                                                                            132
PS
        TTB
                 MECH
                         RAD
                                20C/60D, 65C/5H, GR: 0.5-5H
                                                                                            132
PS
        TTB
                 OIL
                         RAD
                                 APP. 23C/60D. 65C/5H. GR: TO 65C/TO 60D
                                                                                             39
PS
        TTB
                 CIL
                         RAD
                                 200/30,600
                                                                                             45
PS
        TTB
                 OIL
                         RAD
                                 4-25%DDP. APP. 20C/30.60D. 40C/10D. GR: TO 80C/TO 80D
                                                                                             46
PS
        TTB
                 CIL
                         RAD
                                 65C/2.5H. GR: TO 6H
                                                                                             51
                 CIL
                         RAD
                                 20C/30.60D, GR: TO 60D
PS
        TTB
                                                                                             52
PS
                 CIL
                                 APP. FAT-PENETRATION. 20C/30.60D. 65C/2.5H
        TTB
                         RAD
                                                                                             53
PS
        TTB
                 CIL
                         RAD
                                 20C/43,60D
                                                                                             54
P5
        TTB
                 CIL
                         RAD
                                 200/60D. 650/5H. GR: 0.5-5H
                                                                                            132
                                 4-25%DOP, APP, 20C/30,60D, 40C/10D, GR: TO 80C/TO 80D
PS
        TTB
                 42C
                         RAD
                                                                                             46
PS
        778
                 R20
                         RAD
                                 20C/43,60D
PS
        TTB
                 TG
                         RAD
                                 65,83C/2,5H
                                                                                             38
        TTB
PS
                 TG
                         RAD
                                 200/30,600
                                                                                             45
PS
        TTB
                 TG
                         RAD
                                65C/2.5H. GR: TO 6H
                                                                                             51
PS
        TTB
                 TG
                         KAD
                                 20C/30.63D. GR: TO 60D
                                                                                             52
                                 APP. FAT-PENETRATION. 20C/30.60D. 65C/2.5H
                         RAD
PS
        TTR
                 TG
                                                                                             53
PS
        XYZ
                 H20
                                 TO 50C/TO 8W
                                                                                            119
PS
        XYZ
                                                                                            100
PS
        XYZ
                                CMT. SD
                                                                                            172
PU
        CHBP
                         RAD
                                D. H#. SMEAR. 36-75C/TO 30D
                                                                                             69
PU
        HOBP
                         RAD
                                 D. h*. SMEAR, 36-75C/TO 30D
                                                                                             59
PVC
        ABC
                 ET20
                         GC
                                 NKD. TO 98C/TO 10D
                                                                                             10
PVC
                                 NKD, TO 98C/TO 10D
        ABC
                 HC
                         GC
                                                                                             10
PVC
        ABC
                 CIL
                         GC
                                 NKD. 70 98C/TO 100
                                                                                             10
PVC
        ABC
                 TG
                         GC
                                 NKD, TO 98C/TO 10D
                                                                                             10
PVC
        ABC
                                 20C/1.3.7D
PVC
        ACA
                 DIL
                                 4.20-25C/1.2.3.6M. 45C/10D
                                                                                            167
PVC
        EPBG
                                 200/103070
                                                                                             83
                 ETOH
PVC
        ETA
                         TLC
                                NKD. 45C/10D
                                                                                            170
PVC
        ETA
                HC
                         TLC
                                NKD. 45C/10D
                                                                                            170
PVC
        ETA
                HC
                                 GR: 40-65C/TO 60D
                                                                                            118
        ETA
PVC
                         TLC
                 H2C
                                 NKD. 45C/10D
                                                                                            17)
PVC
        ETA
                HOAC
                         TLC
                                 NKD: 45C/10D
                                                                                            170
PVC
        ETA
                CIL
                         POLAR 4.20-25C/1.2.3.6M. 45C/10D.6M
                                                                                            166
PVC
        ETA
                 CIL
                         TLC
                                 NKD, 45C/10D
                                                                                            170
PVC
        ETA
                 CIL
                                 GR: 40-65C/TD 60D
                                                                                            118
PVC
                         SPEC
        CAST
                H2C
                                5,50C/2,4,6,8W
                                                                                             30
                ETCH
PVC
        DBP
                         RAD
                                 25C/TO 50D
                                                                                             79
                                 20-60PHR. 10-67C/1-80D
PVC
        CBP
                ETOH
                         RAD
                                                                                             80
PVC
        062
                 ET20
                         GC
                                NKD, TO 98C/TO 10D
                                                                                             10
PVC
        DBP
                 HC
                         GC
                                NKD. TU 98C/TO 100'
                                                                                             10
                                2J-60PHR. 10-60C/2-80D
PVC
        DBP
                 HC
                         RAD
                                                                                             79
PVC
        DBP
                 MEGH
                         RAD
                                 20-60PHR, 10-60C/1-80D
                                                                                             80
PVC
        DBP
                 CIL
                         GC
                                 NKD, TO 98C/TO 10D
                                                                                             10
PVC
        DBP
                 CIL
                         RAD
                                 25-63PHR, 10-60C/1-70D
                                                                                             81
PVC
        CBP
                 ROH
                         RAD
                                 20-60PHR . 10-60C/1-80D
                                                                                             80
                        • GC
PVC
        DBP
                 TG
                                 NKD, TO 98C/TO 10D
                                                                                             10
PVC
        DBP
                         RAD
                                 23-60PHR: 10-60C/1-70D
PVC
        CBS
                                 20C/1.3.7D
                                                                                             23
PVC
        DBSN
                 AQ
                                 500/2.4.6W
                                                                                            125
PVC
        DBSN
                 ETCH
                                 50C/2.4.6W
                                                                                            125
PVC
        CBSN
                 FC
                                 500/20406W
                                                                                            125
PVC
                         SPEC
        DBSN
                H20
                                 5.50C/2.4.6.8W
                                                                                             3)
PVC
        DBSN
                                                                                            125
                 HOAC
                                 50C/2.4.6W
PVC
        DNP
                                 ENI, 38-56C/TQ 12D
                 AQ
                                                                                             86
PVC
        DNP
                 AC
                                 NKD. 20-56C/TO 15D
                                                                                            182
PVC
        DNP
                 AQ
                                 ENI, 40-80C/TO 20D
                                                                                            183
```

				•	
PVC	DNP	DP		ENI . 38-56C/TO 12U	36
PVC	DNP	DP		NKD. 23-56C/TU 15D	182
PVC	DNP	DP		20-60C/TO 20D, ENI	184
PVC	DNP	DP		40-70C/TO 120. ENI	185
PVC	DNP	H20		ENI, 38-56C/TD 12D	86
PVC	DNP	H20		NKD: 20-56C/T0 150	182
PVC	DNP DDP	H2O AC		40-73C/TO 12D, ENI	185
PVC	DCP	BL	GC	50C/2.4.6W NS. 4C/5-21D	125
PVC	DCP	ETOH	RAD	25C/T0 53D	78
PVC	DCP	ETCH	RAD	20-60PHR • 10-60C/1-80D	83
PVC	DOP	ETOH	TLC	NKD: 1-5%DOP: 45C/2D	188
PVC	DCP	ETCH		50C/2:4:6W	125
PVC	DOP	ET20	GC	NKD. TO 98C/TO 10D	10
PVC	DOP	ET20	TLC	NKD + 1-5%DCP+ 45C/2D	188
PVC	DCP	FC	GC	NKD. TO 98C/TG 10D	1.0
PVC	DOP	HC	RAD	20-60PHR. 10-60C/2-80D	79
PVC	DOP	HC	TLC	NKD. 1-5%DGP. 45C/2D	138
PVC	DOP	HC		5JC/2,4,6W	125
PVC	DOP	H2G	GC	1C UC/6H	18
PVC	DOP	H2C	RAD	GR: 22-80C/5H-90D	12
PVC	DOP	H2G	TLC	NKD+ 1-5%DCP+ 45C/2D	158
PVC	DOP	HCAC		5JC/2.4.6W	125
PVC	DGP	MECH	RAD	23-60PHR • 10-60C/1-80D	83
PVC	DOP	OIL	GC	NKD. TO 98C/TO 10D	. 10
PVC	DOP	CIL	RAD	APP. NKD. 0.25-25%, 20C/60D. 40C/10D	40
PVC	DCP	CIL	RAD	APP. 0.25-25%DOP. GR: TO 43C/TO 30D	43
PVC	DOP	CIL	RAD	20-60PHR. 10-69C/1-70D	81
PVC	DOP DCP	OIL	RAD	NKD. AFP. CMT. SECT. CP. FAT-MIGRATION. 40C/1.2.4.9.16.25D	92
PVC	DCP	RCH	RAD	20-60PHR 10-60C/1-80D	130
PVC	DOP	TG	GC	NKD. TO 98C/TO 10D	1)
PVC	DOP	10	RAD	2G-6CPHR 10-60C/1-70D	81
PVC	DCP			INTER-POLYMER, APP, 70C/TO 1320D	112
PVC	DCSN	AQ		ENI. 38-56C/TC 12D .	86
PVC	DOSN	AQ		ENI. 40-89C/TO 20D	183
PVC	DOSN	DP		ENI. 38-56C/TO 12D	86
PVC	DGSN	DP		2C-60C/TD 20D. ENI	184
PVC	DCSN	DP		40-70C/TO 12D. ENI	185
PVC	DCSN	ETCH	RAD	NKD. 20C/8W	91
PVC	DCSN	ET20	GC	NKD. TO 98C/TD 10D.	10
PVC	DOSN	ET2C	RAD	20C/60D. 65C/5H. GR: 0.5-5H	132
PVC	DOSN	FHC	RAD	2UC/43.60D	54
PVC	DCSN	HC	GC	NKD. TO 98C/TO 10D	13
PVC	DCSN	HC	RAD	4-25%DOP, APP, 20C/30.60D, 40C/10D, GR: TO 80C/TO 80D	46
PVC	DCSN	HC	RAD	2JC/43,60D	54
PVC	DOSN	HC	RAD	2)C/6)D, 65C/5H, GR:),5~5H	132
PVC	DCSN	H2C	SPEC	5.5JC/2.4.6.8W	30
PVC	DCSN	H2C		ENI, 38-56C/TC 12D	86
PVC	DOSN	H2C	F. A D	46-70C/TO 120. ENI	185
PVC	DOSN	MECH	RAD	21C/60D, 65C/5H, GR: 0.5-5H	132
PVC	DCSN DCSN	CIL	GC RAD	NKD. TO 98C/TO 10D APP. 20C/60D. 65C/5H. GR: TO 65C/TO 60D	39
PVC	DOSN	CIL	RAD	APP. 0.25-25%DOP. GR: TO 40C/TO 30D	43
PVC	DCSN	GIL	RAD	20C/30.60D	45
PVC	DOSN	CIL	RAD	4-25%DOP, APP, 20C/34.60D, 40C/10D, GR: TD 80C/TD 80D	46
PVC	DCSN	CIL	RAD	NKD, 4-25%DOP, 40C/10D, APP	48
PVC	DESN	CIL	RAD	65C/2,5H, GR: TD 6H	51
_					

```
PVC
        DOSN
                 CIL
                         RAD
                                 200/30.60D. GR: TG 60D
                                                                                               52
                                 AFP. FAT-PENETRATION. 200/30.600. 650/2.5H
PVC
        DOSN
                 CIL
                         RAD
                                                                                              53
PVC
        DCSN
                 CIL
                         RAD
                                 20C/43,60D
                                                                                              54
                          RAD
PVC
        DOSN
                 CIL
                                 GR: 20-40C/0.1-30D
                                                                                               55
PVC
        DCSN
                 CIL
                          RAD
                                 200/630, 650/5H, GR: 0.5-5H
                                                                                              132
PVC
        DCSN
                 CIL
                          RAD
                                 20C/30D. 45C/10D. NKD
                                                                                              155
PVC
        DCSN
                 CIL
                         RAD
                                 NKD. J.10.20.30.45C/10D. 75C/2D
PVC
        DCSN
                 OIL
                                 4.23-25C/1.2.3.6M. 45C/10D
                         RAD
PVC
        DCSN
                 R20
                                 4-25%DDP, APP, 20C/30,600, 40C/10D, GR: TO 83C/TO 80D
                                 200/43,600
PVC
        DCSN
                 R20
                         RAD
                                                                                               54
                          GC
                                 NKD. TC 98C/TO 100
PVC
        DCSN
                 TG
                                                                                               10
                                 65,83C/2,5H
PVC
        DCSN
                 TG
                         RAD
                                                                                               39
PVC
                                 200/30,600
        DCSN
                 TG
                         RAD
                                                                                               45
                                 65C/2.5H. GR: TO 6H
                 TG
                         RAD
PVC
        DCSN
                                                                                               5.1
                                 20C/30.60D. GR: TO 60D
PVC
        DCSN
                 TG
                         RAD
                                                                                               52
                                 APP. FAT-PENETRATION. 20C/30.60D. 65C/2.5H
PVC
                 TG
                         RAD
        DOSN
                                                                                              53
PVC
        HMBP
                 ETOH
                         TLC
                                 NKD. 45C/10D
                                                                                             173
PVC
        HMBP
                 HC
                          TLC
                                 NKD, 45C/10D
                                                                                              175
                                 NKD. 45C/10D
PVC
        FMBP
                 F20
                         TLC
                                                                                             175
PVC
        HMBP
                 HCAC
                         TLC
                                 NKD: 45C/10D
                                                                                              170
                                 NKD. 45C/10D
PVC
        HMBP
                 OIL
                          TLC
                                                                                              170
PVC
        MGST
                 H20
                         SPEC
                                 5.50C/2.4.6.8W
                                                                                               33
                          RAD
PVC
        MMBP
                                 D. K. INTER-POLYMER
                                                                                               13
PVC
                 H2C
                          SPEC
                                 5.50C/2.4.6.8W
        MSN
                                                                                               30
PVC
        MSN
                 CIL
                         RAD
                                 20C/30D. 40C/10D. 70C/0.5H. GR: TO 30D
PVC
        MSN
                 CIL
                          RAD
                                 40C/5-240H
                                                                                               44
                                 ENI, 38-56C/TO 12D
PVC
        PAP
                 AQ
                                                                                               86
PVC
        PAP
                 AQ
                                 NKD: 20-56C/TO 15D
                                                                                              182
PVC
        PAP
                 AQ
                                 ENI. 43-80C/TU 20D
                                                                                              183
PVC
        PAP
                 DP
                                 ENI. 38-56C/TO 12D
                                                                                               86
PVC
        PAP
                                                                                              182
                 DP
                                 NKD. 20-56C/TC 15D
        PAP
PVC
                 DP
                                                                                              184
                                 20-60C/TO 20D. ENI
                 DP
                                 40-70C/TO 12D. ENI
PVC
        PAP
                                                                                              185
PVC
        PAP
                 H2G
                                 ENI, 38-56C/TO 12D
                                                                                               86
                                                                                              182
        PAP
                                 NKD, 20-56C/TO 15D
PVC
                 F-20
        PAP
                                                                                              185
PVC
                 H20
                                 40-70C/TO 12D, ENI
        PB
                                 NC .
                                                                                              165
PVC
                                         20-80C
                                 ENI. 38-56C/TO 12D
                                                                                               85
PVC
        RSE
                 AQ
PVC
                                                                                              183
        RSE
                 AG
                                 ENI. 40-80C/TO 20D
PVC
                 DP
                                                                                              86
        RSE
                                 ENI. 38-56C/TO 12D
PVC
        RSE
                 OP
                                 25-60C/TO 20D. ENI
                                                                                              134
PVC
        RSE
                 DP
                                 40-70C/TO 12D. ENI
                                                                                              185
PVC
        RSE
                 H20
                                 ENI. 38-56C/TO 12D
                                                                                               86
                                 43-70C/TO 12D. ENI
                                                                                              185 .
PVC
        RSE
                 H20
PVC
         SN
                 ETCH
                          COLOR
                                 RT/1-138H. SURFACE-WASH
                                                                                               34
PVC
                 ETZO
                                 RT/C.5.1.11M
                                                                                              183
         SN
PVC
                                 RT/C.5.1.11M
                                                                                              180
         SN
                 HC
                        * COLOR
PVC
         SN
                 H2C
                                 RT/1-138H, SURFACE-WASH
                                                                                               34
PVC
         SN
                 HCAC
                                 APP. NC. NS. NTT
                                                                                                Ĩ.
                                                                                              185
PVC
         SN
                 CIL
                                 RT/0.5.1.11M
PVC
         SN
                 VEG
                                 APP. NC. NS. NTT
                                                                                               8
PVC
        TEP
                 H2C
                          RAD
                                 GR: 22-80C/5H-93D
                                                                                               12
                                                                                               39
                                 5.50C/2.4.6.8W
PVC
        TIC2
                 H20
                          SPEC
                                                                                              132
PVC
        TTB
                 ET20
                          PAD
                                 24C/60D. 65C/5H. GR: 0.5-5H
PVC
        TTB
                 F.C
                                 20C/60D. 65C/5H. GR: 0.5-5H
                                                                                              132
                          CAR
                                                                                              132
PVC
        TTR
                 MECH
                          SAD .
                                 24C/60D. 65C/5H. GR: 0.5-5H
                                 AFP. 23C/63D. 65C/5H. GR: TO 65C/TO 60D
PVC
        TTB
                 CIL
                          RAD
                                                                                               39
PVC
         TTB
                 CIL
                          RAD
                                 2JC/30.60D
```

```
PVC
        TTB
                 CIL
                          RAD
                                  65C/2.5H. GR: TD 6H
                                                                                                 51
PVC
         TTB
                 CIL
                          RAD
                                  20C/30.60D. GR: TO 60D
                                                                                                 52
PVC
         TTB
                 CIL
                          RAD
                                  APP, FAT-PENETRATION, 20C/30,60D, 65C/2,5H
                                                                                                 53
PVC
                                  20C/60D, 65C/5H, GR: 0.5-5H
         TTB
                 CIL
                          HAD
                                                                                                132
PVC
         TTB
                 TG
                          RAD
                                  65,83C/2,5H
                                                                                                 38
PVC
         TTB
                 TG
                          RAD
                                  20C/30.60D
                                                                                                 45
PVC
         TTB
                 TG
                                  65C/2.5H. GR: TD 6H
                          RAD
                                                                                                 51
PVC
         TTB
                 TG
                          RAD
                                  20C/30.60D. GR: 70 60D
                                                                                                 52
PVC
         TTB
                 TG
                          FAD
                                  APP, FAT-PENETRATION, 20C/30,600, 65C/2,5H
                                                                                                 53
PVC
         VC
                 ETCH
                          GC
                                  NS. 22C/3.6.9.12M. GR: TO 49C/TO 10Y
                                                                                                 27
PVC
         VC
                 ETCH
                          GM
                                  SGL. SD. 30-90C
                                                                                                  7
                                  GR: 23-70C/C.01-720D
PVC
         VC
                 ETCH
                                                                                                131
PVC
         VC
                          GC
                                  NS, 22C/3,6,9,12M, GR: TO 49C/TO 10Y
                 H.C
                                                                                                 27
PVC
         VC
                 H.C
                          GC
                                  K, S/D
                                                                                                116
PVC
         VC
                                  NS, 22C/3,6,9,12M, GR: TD 49C/TO 10Y
                 F20
                          GC
                                                                                                 27
PVC
         ٧C
                                  K. CMT. SD
                 F20
                          GC
                                                                                                 62
PVC
         VC
                 H2C
                                  K. SD. AC
                                                                                                 63
                          GC
PVC
         VC
                                  K. S/D
                 ⊁20
                          GC
                                                                                                116
                                  SCL. SD. 30-90C
PVC
         ٧C
                                                                                                  7
                 H<sub>2</sub>C
                          GM
PVC
         VC
                                                                                                  5
                 H<sub>2</sub>C
                                  MC. 23C/1-180D
PVC
         VC
                                  GR: 23-76C/8.01-720D
                                                                                                131
                 H2C
                                  NS, 220/3,6,9,12M, GR: TO 490/TO 10Y
PVC
         VC
                 HOAC
                          GC
                                                                                                 27
PVC
         VC
                 HOAC
                          GC
                                  K. SD. AC
                                                                                                 63
PVC
         VC
                                  GR: 23-70C/0.C1-720D
                                                                                                131
                 HOAC
                                                                                                 93
PVC
         VC
                 OIL
                          GC
                                  40C/10.20D. RT/35D. GR: TO 160D. CP
                                                                                                 27
PVC
         VC
                 OIL
                          GC
                                  NS. 22C/3.6.9.12M. GR: TO 49C/TO 10Y
PVC
         VC
                 CIL
                          GC
                                  K. CMT. SD
                                                                                                 62
PVC
         VC
                 CIL
                          GC
                                  K. S/D
                                                                                                116
                                  GR: 23-70C/C.C1-720D
                                                                                                131
PVC
         VC
                  CIL
PVC
         VC
                          GC
                                  AIR, MODEL, GR: TO 38C/TO 30D
                                                                                                 26
PVC
         ٧C
                          GM
                                  C. SD. CMT. 20-90C
                                                                                                  -3
PVC
         ZNST
                 H2C
                          RAD
                                  GR: 22-80C/5H-90D
                                                                                                 12
PVC
                 MF
                           GC
                                  4C/1,2,8,4D
                                                                                                 28
PVDC
         DCP
                 OIL
                                  AFP, CMT, SECT, CP, FAT-MIGRATION, 40C/1,2,4,9,16,25D
                                                                                                130
PVDC
                 ETCH
                                  GR: 23-70C/0.01-720D
                                                                                                131
                                                                                                131
PVDC
                 H2C
                                  GR: 23-70C/C.01-720D
                                                                                                131
PVDC
                 HOAC
                                  GR: 23-70C/C.01-720D
PVDC
                 CIL
                                  GR: 23-70C/C.01-720D
                                                                                                131
                                                                                                131
SAN
         AN
                 ETCH
                                  GR: 23-70C/C.01-720D
                                                                                                131
SAN
         AN
                 F.2C
                                  GR: 23-70C/C.01-720D
                                                                                                131
SAN
         AN
                 HCAC
                                  GR: 23-70C/C.61-720D
                                                                                                131
SAN
         AN
                  CIL
                                  GR: 23-70C/0.01-720D
                                                                                                141
SBR
         BCO
                                  D
SBR
                                  D. CMT
                                                                                                139
         HXD
SBR
         MW
                           GM
                                  BLCOM
                                                                                                158
SBR
                                                                                                 19
         WAX
                                  TO 280D
V/AP8
                 H2G
                                  6UC/1H. NKD
                                                                                                 20
         VAC
V/AP8
         VC
                  ETCH
                                                                                                  14
                                                                                                  14
V/APB
         ٧C
                 h2C
PAN
         AN
                 H2C
                          GC
                                  K. SD. AC
                                                                                                 63
                                                                                                 63
PAN
         AN
                  FOAC
                           \mathsf{GC}
                                  K. SD. AC
PVC/ABS AN
                  ETCH
                           PULAR
                                  NKD. RT/4D
                                                                                                 95
                                                                                                  95
                           PCLAR
PVC/ABS AN
                 H2C
                                  NKC. RT/4D
                                                                                                  95
PVC/ABS AN
                  HOAC
                           PCLAR
                                  NKD. RT/4D
                  CIL
                           PCLAR
                                  NKC. RT/4D
                                                                                                  95
PVC/ABS AN
                                                                                                 95
PVC/ABS EST
                  ETCH
                           PCLAR
                                  NKD. RT/4D
                                                                                                  95
PVC/ABS EST
                 H2C
                           PCLAR
                                  NKC. RT/4D
                                                                                                  95
PVC/ABS BST
                 HOAC
                           PCLAR
                                 NKD. RT/4D
```

PVC/ABS	est	CIL	POLAR	NKD. RT/4D	95
PVC/ABS		ETCH	PCLAR	NKC, RT/4D	95
PVC/ARS		H2C	POLAK	AKC. RT/4D	95
PVC/ABS	DCP	HCAC	PCLAR	AKD. RT/4D	95
PVC/ABS	DOP	CIL	PCLAR	NKC. RT/4D	95
PVC/ABS	s	ETCH	PCLAR	NKD, RT/4D	95
PVC/ABS	S	H2C	PCLAR	NKC. RT/40	95
PVC/ABS	s	HCAC	POLAR	NKD. RT/4D	95
PVC/ABS	S	CIL	PCLAR	NKC, RT/4D	95
PAT	XYZ	CIL	RAD	APP, 40C/10D	1:35
PES	XYZ	H20		TC 50C/TO 8W	119
ABS/MA		ETCH		39-65C/1-7D. NKD	179
ABS/MA		H20		39-65C/1-7D, NKD	179
ABS/MA		HOAC		39-65C/1-7C. NKD	179
ABS/MA				39-65C/1-70, NKD	179
				APP .	41
				APP	49

LITERATURE REFERENCE

- 1. Adcock, L.H.

 New Test Tells How Additives in Packages Migrate into Food

 Package Eng., Vol. 21, No. 9, pp. 45-6 (1976)
- 2. Alfrey. To. Gurnee. E.F., and Lloyd. W.R. Diffusion in Glassy Polymers
 J. Polym. Sci. C. Vol. 12, pp. 249 (1966)
- 3. Asada. T., Inoue. K., and Onogi, S.

 Diffusion in the Nylon 12 and Water System

 Polymer J., Vol. 8, No. 1, pp. 21-29 (1975)
- 4. Bagdonaite, V.A., and Yushkevichyute, S.S.

 Migration of Antioxidants between Polyethylene and PVC

 Plast. Massy, No. 9, pp. 53 (1975); Intl. Poly. Sci. Technol.

 Vol. 3, No. 2, pp. 70 (1976)
- 5. Banzer. J.D.
 The Migration of Vinyl Chloride Monomer from PVC Pipe into Water Soc. Plast. Eng. NATEC. Nov. 1977. pp. 33-34
- 6. Bent. h.A.. and Pinsky. J.

 Theoretical Investigation of the Mechanism of Transfer of Materials through Polyethylene

 Wright Air Development Center. Technical Report 53-133, Pt. 2 (1955)

- 7. Berens, A.R.

 The Solubility of Vinyl Chloride in Poly(vinyl chloride)

 Polymer Preprints, Vol. 15, pp. 197 (1974)
- 8. Berens, A.R.
 The Diffusion of Vinyl Chloride in Poly(vinyl chloride)
 Polymer Preprints, Vol. 15, pp. 203 (1974)
- 9. Berens, A.R., and Caniels, C.A.
 Prediction of Vinyl Chloride Monomer Migration from Rigid PVC Pipe
 Polym. Eng. Sci., Vol. 16, No. 5, pp. 52 (1976)
- 10. Bergner, K.G., and Berg, H.

 Migration of Additives from Plastics in Triglycerides Compared
 with their Extractability by Organic Solvents

 Dtsch. Lebensm.-Rundsch., Vol. 68, No. 9, pp. 282-8 (1972)
- 11. Bethune, J.L.

 Directed Transport of Monomer-Single Polymer Systems. Comparison of the Countercurrent Analog and Asymptotic Approaches

 J. Phys. Chem., Vol. 74, No. 22, pp. 3837-45 (1970)
- 12. Bloom. P.J.

 Contribution to the Investigation into the Migration into Liquid
 Foods of Auxiliary Substances Used in Plastics Manufacturing and
 Processing. Part II. Migration of Auxiliary Substances of
 Poly(Vinyl Chloride) into Crinking Water
 Dtsch. Lebensm.-Rundsch., Vol. 72, No. 6, pp. 194-7 (1976)
- 13. Bobrovskaya, T.S., Markelov. M.A., and Semenenko, E.I. Migration of Dioctyl Phthalate from Plasticised PVC into Water Plast. Massy. No. 4. pp. 56 (1974); Intl. Polym. Sci. Technol., Vol. 1, No. 7, pp. 10 (1974)
- 14. Boikova: ZeKe: and Petrova: L.I. Migration of Vinyl Acetate from Copolymers Based on it Plaste Massy, No. 12. pp. 43 (1976): Intl. Polym. Sci. Technol.. Vol. 4. No. 5. pp. 35 (1977)
- 15. Booher, T.R., and Stringer, C.D.

 Study of Additive Migration from Films to Food by 14C-Labeling ACS Abstr., Div. Crg. Coat. Plast., Vol. 152, pp. T22 (1966)
- 16. Botre, C., D'Antoni, L., Memoti, A., and Pallotti, G. Chemical. Technicopharmaceutical and Legislative Aspects on the Transfusion Blood and its Components, Note II. Extraction of Plasticizers from Blood in the Poly(Vinyl Chloride) Containers Rass. Chim., Vol. 27, No. 5, pp. 245-8 (1975)
- 17. Brit. Plast. Fed., and Brit. Ind. Biol. Res. Assoc.
 Plastics for Food Contact Applications. A Code of Practice for
 Safety in Use
 London, pp. 54 (1969)
- 18. Broitman, A.Ya., Putilina, L.V., and Podval'naya, E.K.
 Toxicolgy of Vinyl Acetate-Vinyl Pyrrolidone Copolymers
 Plast. Massy, No. 12, pp.48 (1976); Intl. Polym. Sci. technol.,
 Vol. 4, No. 6, pp. 50 (1977)

- 19. Brown. D.W., and Lowery, R.E.

 Herny's Law and Diffusion Constants of Vinyl Chloride in

 Poly(vinyl chloride) at High Temperature

 J. Polyme Sci., Polyme Chem. Sect., Vol. 15, pp.2623-39 (1977)
- 20. Bruck, C.G. vom, Eckert, W.R., and Rudolph, F.B.

 Migration of Vinyl from PVC Packaging
 Fette. Seifen, Anstrichem., Vol. 78, No. 8, pp. 334-7 (1976)

 Intl. Polym. Sci. Technol., Vol. 3, No. 10, pp. 103 (1976)
- 21. Bruck. C.G. Vom. Figge. K., Piater, H., and Wolf. V.

 Migration of Plastics-Processing Adjuvant Substances from Films into Liquid and Solid Fats and Simulants. IX. Results of Previous Extraction and Migration Studies

 Dtsch. Lebensm.-Rundsch., Vol. 67, No. 12, pp. 444-52 (1971)
- 22. Chalyukh. A.E.

 Diffusion of Monomers in Polymers

 Vysokomot. Soedin., Ser. 8, Vol. 17, No. 3, pp. 215-19 (1975)
- 23. Chantrey. G., and Rattee, I.D.
 Influence of Polymer and Dye Characteristics on Diffusion in Nylon 66
 J. Appl. Polym. Sci., Vol. 18, No. 1, pp. 93-153 (1974)
- 24. Code of Federal Regulations. Title 21. Food and Drugs
 Part 175. Indirect Food Additives: Adhesive Coatings and Components
 Part 176. Indirect Food Additives: Paper and Paperboard Components
 Part 177. Indirect Food Additives: Polymers
 April 1. 1977
- 25. Chernova. T.V.

 Hygienic Evaluation of SNP-2P Polystyrene Containers Intended for Packaging Foodstuffs

 Vopr. Pitan., Vol. 30. No. 5. pp. 56-58 (1971)
- 26. Crider, L.B., O'Mara, M.M., and Bowles, R.L.

 A Model for the Diffusion of Vinyl Chloride Monomer from PVC

 Under Various Conditions of Storage

 Soc. Plast. Eng. NATEC, Nov. 1977, 195-9
- 27. Daniels, G.A., and Proctor, D.E.

 VCM (Vinyl Chloride Monomer) Extraction from PVC Bottles

 Mod. Packag., Vol. 48, No. 4, pp. 45-8 (1975)
- 28. Daun. H., and Gilbert, S.G.
 Migration of Plasticizers from Poly(vinyl chloride) Packaging Films
 to Meat

 J. Food Sci., Vol. 42. No. 2, pp. 561-2 (1977)
- 29. Davies, J.T.

 Migration of Styrene Monomer from Packaging Materials in Food.

 Experimental Verification of a Theoretical Model

 J. Food Technol., Vol. 9, No. 3, pp. 275-83 (1974)
- 30. Dietz, G.R., Banzer, J.D., and Miller, E.M. Water Extraction of Additives from PVC Pipe

Soc. Plaste Eng. NATEC, Nov. 1977, pp. 25-9

31. Dotreppe-Grisard. No

Control of the Migration of Adjuvants of Plastic Materials in Food Liquids

Tribo Cebedeau (Cento Belge Etude Doco Eaux), Volo 25, No. 341, pp. 198-201 (1972)

32. Dotsenko. V.A., and Shiba. V.V.

Methods for a Sanitary-Chemical Evaluation of Polymeric Materials and Products Made from them in Contact with Foods and Drinks Gigo Sanita Volo 13. pp. 90-2 (1972)

33. Downes, Toko

The Mechanism of the Migration of Organotin Stabilizer from Poly(vinyl chloride) into Containing Media Diss. Abstr. Int., 8. Vol. 33. No. 8, pp. 3792: Order, No. 73-4740 (197.

34. Downes, T.W., and Cilbert, S.G.

The Effect of Surface Treatments on the Migration of Organotin Stabilizer from Poly(vinyl chloride) Films to Contacting Liquid Media

Dtsch. Lebensm.-Rundsch.. Vol. 71. No. 12, pp. 422-425 (1975)

- 35. Easterling, R.E., Johnson, E., and Napier, E.A., Jr.

 Plasma Extraction of Plasticizers from Medical Grade

 Poly(vinyl chloride) Tubing

 Proc. Soc. Exp. Biol. Med., Vol. 147, No. 2, pp. 572-4 (1974)
- 36. Evstatieva, M.

 Migration of Some Azo Dyes from Prepared Polymer Materials

 Khigo Zdraveopazo, Vol. 16, No. 5, pp. 479-82 (1973)
- 37. FDA Guidelines for Chemistry and Technology.

 Requirements of Food Additives Petitions
 Bureau of Science, FDA, HEW (August 1966)
- 38. Figge, K.

 Migration of Processing Aids from Plastic Film into Food Fats

 Kunststoffe, Vol. 61, No. 11, pp. 832-8 (1971)
- 39. Figge, K.

 Migration of Additives from Plastic Films into Edible Dils and
 Fat Simulants

 Food Cosmet. Toxicol., Vol. 10, No. 6, pp. 815-28 (1972)
- 40. Figge, K.

 Determination of Total Migration from Plastics-Packaging Materials in Edible Fasts Using a Carbon-14-Labeled Fat Simulant Food Cosmet. Toxicol., Vol. 11, No. 6, pp. 963-74 (1973)
- 41. Figge. K.

 Method for the Determination of the Total weight of All Components

 Migrating from Packaging Material into Edible Fats. the So-Called

 Total Migrate. Using Fat Simulant HB 307-(14)C

 Otsch. Lebensm.-Rundsch., Vol. 69, No. 7, pp. 253-7 (1973)
- 42. Figges K.

Migration of Methyltin Thioglycolic Acid Esters from Rigid PVC Packagings into Fat-Containing Foods

Verpack-Rundsch. Vol. 26, No. 8, pp. 59-63 (1975)

43. Figge, K.

Radioanalytic Method for Determining the Passage of Packaging Ingredients nto Foods

J. Radioanal. Chem., Vol. 32. No. 2. pp. 315-43 (1976)

44. Figge. Ko. and Bieber. Wolo

Migration of Methyltin Stabilizer Advastab TM 181 FS from Rigid PVC into Fat Simulant HB 307. II. Migration Behavior of Several Stabilizer Components

Verpack.-Rundsch., Vol. 26, No. 8, pp. 11-22 (1975)

45. Figge, K.. Eder, S.R.. and Piater, H.

Migration of Plastics Processing Additives out of Foils in Liquid

and Solid Fats as well as Simulants. XI. Synthetic Triglyceride

Mixture as General Fat Simulant

Dtsch. Lebensm.-Rundsch., Val. 68, No. 11, pp. 359-67 (1972)

- 46. Figge, K., and Koch, J.

 Effect of Some Variables on the Migration of Additives from Plastics into Edible Fats

 Food Cosmet. Toxicol., Vol. 11, No. 6, pp. 975-988 (1973)
- 47. Figge. K., and Koch, J.

 Determination of the Migration Rate from Plastics onto Nutritional Fats
 by means of a Carbon-14-Labeled Fat Simulating Agent
 Report AEC-Conf-73-461-1. pp. 12 (1973)
- 48. Figge. K., and Koch, J.

 Determination of the Total Plastic Packaging Components Migrating into Edible Cil by Using a Carbon-14-Labeled Fat Simulant Fette. Seifen. Anstrichm., Vol. 77. No. 5, pp. 184-8 (1975)
- 49. Figge, K., and Piater, H.

 Methods of Migration and Extraction Studies with 14C-Labeled

 Additives, III. Migration of Plastic Additives from Films into

 Liquid and Solid Fats and Simulated Fats

 Dtsch. Lebensm.-Rundsch., Vol. 67, No. 1, pp. 9-15 (1971)
- 59. Figge. K., and Fiater. H.

 Migration of Adjunct Materials of Plastics Processing from Films

 Into Liquid and Solid Fats and Similar Substances. IV. Amounts

 of Additives on the Test-Film Surfaces

 Dtsch. Lebensm.-Fundsch.. Vol. 67. No. 2, pp. 47-8 (1971)
- 51. Figge. K.. and Fiater. H.

 Migration of Adjuvants of Plastics Manufacturing from Films into
 Liquid and Solid Fats and Simulated Fats. V. Extraction and
 Short-Term Study Data

 Otsch. Lebensm.-Rundsch.. Vol. 67. No. 4. pp. 11J-19 (1971)
- 52. Figge. K.. and Piater. H.

 Migration of Auxiliary Materials from Plastic Films into Liquid
 and Solid Fats or Fatlike Compounds. VI. Migration and
 Long-Term Tests with Liquid Fats and Fatlike Materials

Dtsch. Lebensm.-Rundsch., Vol. 67, No. 5, pp. 154-61 (1971)

- 53. Figge, K., and Fiater, H.

 Migration of Adjuvants Used in Plastics Manufacture from Films.

 VII. Method and Results of Extraction and Migration Experiments with Solid Edible Fats. Penetration of Adjuvants into Solid Fats.

 Dtsch. Lebensm.-Rundsch., Vol. 67, No. 7, pp. 235-42 (1971)
- 54. Figge. K., and Piater. H.

 Migration of Auxiliary Manufacturing Substances from Films into Liquid and Solid Fat and Simulants. X. Passage of Additives into N-Alkane and Di-n-Alkane Ethers as well as into other Organic Liquids

 Dtsch. Lebensm.-Rundsch., Vol. 68, No. 10, pp. 313-319 (1972)
- 55. Figge. K., and Zeman, A.

 Migration of Tin Stabilizers from Unplasticized PVC Film into FatContaining Foods. X-Ray Photoelectron-Spectroscopic and
 Radioanalytical Examination of PVC Surfaces
 Kunststoffe, Vol. 63, No. 8, pp. 543-50 (1973)
- 56. Franzke. C., Uhde. W.J., and Woggon. H.

 Migration of Antioxidants and Stabilizers from Plastic Packing
 into Edible Cil

 Plaste Kautsch., Vol. 17, No. 5, pp. 327-30 (1970)
- 57. Frawley. J. P.
 Toxicol. Evaluation of Migration of Food Additives
 ACS abstr., Div. Crg. Coating Plast., Vol. 152, 723 (66)
- 58. Frisch. H.L.. Wang. T.T.. and Kwei. T.K. Diffusion in Glassy Polymers II. J. Polym. Sci. A., Vol. 2. No. 7. pp. 879 (1969)
- 59. Fritz. W., and Woggon, H.

 Migration of Carcinogenic hydrocarbons from Carbon-Block Stabilized

 Plastics into Foods

 Z. Gesamte Hyg. Ihre Grenzgeb., Vol. 19, No. 5, pp. 349-352 (1973)
- 60. Ganeva. M., and Radeva. M.
 an Approach and Methods for Determination of Dye Migration from
 Plastic Packing for Food Products
 Khig. Zdraveopaz., Vol. 19, No. 3, pp. 281-5 (1976)
- 61. Gardner. K.L., and Mcnally. G.M.

 Morphology of Polypropylene in Relation to Dye Diffusion
 J. Soc. Dyers Colour., Vol. 93, No. 1, pp. 4-7 (1977)
- 62. Gilbert. S.G.

 Migration of Minor Constituents from Food Packaging Materials

 J. Food Sci., Vol. 41. No. 4, pp. 955-8 (1976)
- 63. Gilbert, S.G., and Giacin, J.R.
 Migration of Indirect Food Additives from Plastic
 Packaging Materials: Physical Chemistry Considerations
 Soc. Plast. Eng. NATEC, Nov. 1977, pp. 35-39
- 64. Guricheva. Z.G.: Rudakova. M.N.

- Effect of the Composition of Polystyrene Plastics on Migration of Low-Nolecular-Weight Substances from them
 Plast. Nassy. No. 12. pp. 39-44 (1970)
- 65. Guricheva. Z.G., Krynskaya, I.L., Rudakova, M.N., and Bukevich, G.M.,

 Toxicclogical Evaluation of the Migration of Phthalocyanine Blue

 Dye from Polyethylene

 Gla. Primen. Polim. Mater. Izdelii Nikh, No. 1, pp. 347-54 (1969)
- 66. Guricheva. Z.G.. Rotenberg. V.V. and Shaulova. N.S. Migration of Lake Red ZHE from high-Pressure Polyethylene Gig. Sanit. No. 6. pp. 94-5 (1974)
- 67. Gutsalyul. V.G.. and Samosova. N.S.

 Migration of Plasticizers from Poly(vinyl chloride) Plastics
 into Salt Water Solution

 Izv. Akad. Nauk Kaz. SSR. Ser. Khim. No. 2, pp. 95 (1962)
- 68. Guzeev. V.V.. Belyakova. L.K.. Khoknlova. M.M., Fomina, T.S., and Lebedev. V.P.

 Migration of Low-Molecular weight Plasticizers from Plasticized Poly(Vinyl Chloride) into Polyethylene

 Plast. Massy. No. 9, pp. 53-2 (1959)
- 69. Hauserman. R.G.. and Johnson. M.

 Diffusion of Stabilizers in Polymers. III.

 2.4-Dihydroxybenzophenone and 2-Hydroxy-4-Octoxybenzophenone in Polyurethanes

 J. Appl. Polym. Sci.. Vol. 20. No. 9. pp. 2533-9 (1976)
- 70. Hemming, D.F., Collins, J.D., and Datyner, A.

 The Effect of Competitive Adsorption on the Rate of Diffusion
 J. Appl. Polym. Sci., Vol. 20, pp. 597-607 (1976)
- 71. Hill. M.P.L., Millard. P.L., and Gwen. M.J.

 Migration Phenomena in Silicone Modified Polystyrene

 ACS Div. Crg. Coat. Plast. Chem. Pap., Vol. 34, No. 1, pp. 334-9 (1974)
- 72. Ingle. G.W.

 Quantitative Aspects of Migration of Food Additives
 ACS Crg. Coat. Plast. Chem., Vol. 152, T21 (1966)
- 73. Jackson. R.A., Oldand, S.R.O., and Pajaczkowski, A. Diffusion of Additives in Polyolefins
 J. Appl. Polym. Sci., Vol. 12, pp. 1297-1309 (1968)
- 74. Jaeger: R.J.

 Extraction. Accumulation. and Metabolism of Phthalate Ester

 Plasticizers from Poly(Vinyl Chloride) Medical Devices

 Ph.D. Thesis. Johns Hopkins Univ., pp. 194 (1971)
- 75. Jaeger, R.J., and Kubin, F.J.

 Migration of a Phthalate Ester Plasticizer from Poly(vinyl Chloride) Blood Bags into Stored Human Blood and its Localization in Human Tissues

 N. Engl. J. Med., Vol. 287, No. 22, pp. 1114-8 (1972)
- 76. Jaeger, R.J., and Rubin, R.J.

- Plasticizers from Plastic Devices: Extraction, Metabolism, and Accumulation by Elological Systems
 Science, Vol. 170, No. 3956, pp. 460-2 (1970)
- 77. Johnson. M., and Westlake, J.F.

 Diffusion of Stabilizers in Polymers. II.

 2-Hydroxy-4-Cctoxybenzophenone in Polyolefins

 J. Appl. Polym. Sci., Vol. 19, No. 6, pp. 1745-54 (1975)
- 78. Kampouris. E.M.
 Study of Plasticizer Migration by Radioactive Labeling
 Rev. Gen. Caoutch. Plast., Vol. 52, No. 4, pp. 289-92 (1975)
- 79. Kampouris, E.M.

 Migration of Plasticizers into Petroleum Cils

 Euro Polymo J., Vol. 11. No. 12. pp. 735-10 (1975)
- 80. Kampouris. E.M.

 Migration of Plasticizers from Poly(Vinyl Chloride) into Edible Uits

 Polym. Eng. Sci., Vol. 16, No. 1, pp. 59-64 (1976)
- 81. Kampouris. E.M., Regas. F., Rokotas. S., Polychronakis, S., and Pantazo Migration of PVC Plasticizers into Alcohols Polymer, Vol. 16, No. 11, pp. 840-4 (1975)
- 82. Karel. M., and Wogan, G.N.

 Migration of Substances from Flexible Containers for Heat Processed

 Foods

 MIT Cambridge Div. of Sponsored Res. Tech., Report No. 4, Jul 1962-Jun
 1963
- 83. Kataeva. S.E., and Kofanov. V.I.

 Determination of Dicarboxylic Acid Esters in Poly(vinyl chloride)

 Film Extracts

 Gig. Sanit., Vol. 36. No. 7, pp. 67-69 (1971); Hyg. Sanit.

 (Eng. Transl.), Vol. 36, No. 7-9, pp. 81-4 (1971)
- 84. Keller, A.A., Sheldon, A.W., and Simmons, I.

 Fast Extraction Tests for Food-Grade (Poly(Vinyl Chloride))

 Mode Package, Vol. 48, No. 8, pp. 42-4 (1975)
- 85. Keller. A.A., Sheldon, A.W., and Simmons, I.L.

 Accelerated Extraction Tests for Food-Grade Uctyltin Stabilized PVC
 Soc. Plast. Eng., Tech. Pap., Vol. 20,, pp. 514-17 (1974)
- 86. Kiermeler, F., Evers, K.-W., and Wildbrett, G.
 Use of Plastics for Foods, XIV. Simulated Practical Test for Milk
 Pipes
 Dtsch. Lebensm.-Rundsch., Vol. 65, No. 19, pp. 385-11 (1969)
- 87. Kim, J.-W., and Iijima, T.

 Diffusion of Dye Mixtures in Nylon 6. Binary Mixtures of
 Disperse Dyes
 J. Appl. Polym. Sci., Vol. 20, pp. 135-113 (1976)5-11 (1969)
- 88. Klein, J.

 Diffusion of Long Molecules through Solid Polyethylene
 I. Topological Constraints

- J. Polym. Sci., Polym. Phys. Sect., Vol. 15, 2057-64 (1977)
- 89. Klein. J. and Briscoe, B.J.

 Diffusion of Long Molecules Through Solid Polyethylene

 II. Measurements and Results

 J. Polym. Sci., Polym. Phys. Sect., Vol. 15, 2065-74 (1977)
- 90. Knibbe, D.F.

 Theory of Extraction of Additives from Plastics by Swelling Solvents

 Plastica, Vol. 24, No. 8, pp. 358-63 (1971)
- 91. Koch, J., and Figge, K.

 Migration of Tin Stabilizers from PVC Bottles into Beer
 Z. Lebensm.-Unters. Forsch., Vol. 147, No. 1, pp. 8-10 (1971)
- 92. Koch, J., and Figge, K.,

 Decreasing the Fat Simulant Quantity in Migration Investigations on Plastics

 Dtsch. Lebensm.-Rundsch., Vol. 70, No. 6, pp. 237-8 (1974)
- 93. Koch, J. and Figge, K.

 Alteration of the Composition of Fats by Contact with Plastics and its Effect on the Accuracy of the Total Migration Determination Methods

 Dtsch. Lebenm.-Rundsch., Vol. 71, No. 5, pp. 170-7 (1975)
- 94. Koch. J., Robinson, L., and Figge, K.,

 Determination of Fat Release by Foods. I. Methods

 Fette, Seifen, Anstrichm., Vol. 78, No. 9, pp. 371-7 (1976)
- 95. Komatsu. Y., Namiki, T., and Mori, F.

 On the Extractability of Di-Alkyl Tin Compounds from Rigid
 Poly(vinyl Chloride) Containers

 J. Food Hyg. Soc. Jpn. (Shokuhin Eiseigaku Zasshi), Vol. 11,
 No. 1, pp.17-22 (197)
- 96. Komarova. E.N., and Maksimova. N.S.

 Hygenic Properties of PVC/AES compositions

 Plast. Massy. No. 12. pp. 29 (1976) Intl. Polym. Sci. Technol.,

 Vol. 4. No. 5, pp. 5 (1977)
- 97. Kotova: V.N., Koval'chuk, V.M., Platonova, T.V.,
 Tsivinskaya, L.K., and El'tsefon, B.S.
 Toxicity Investigation of Polyformaldehyde Plastics
 Soviet Plastics, Vol. 1972, No. 1, pp. 74-6 (1972)
- 98. Kovgan, N.A.

 Hygienic Evaluation of Metalit Utensils for Food Products
 Vopr. Pitan., Vol. 28. No. 4, pp. 75-76 (1969)
- 99. Kwei: T.K., and Zupko. H.N.

 Diffusion in Glassy Polymers I.

 J. Polym. Sci. A., Vol. 2, No. 7, pp. 867 (1969).
- 100 · Kwei · T · K ·
 Diffusion in Glassy Polymers VI ·
 J · Polym · Sci · A · · Vol · 2 · No · 16 · pp · 1849-1851 (1972)

- 101. Kwei. T.K., and Wang. T.T.

 Diffusion in Glassy Polymers

 Polyme Scie Technolo, Vole 6, Permeability Plaste Films Coate Gases.

 Vapo, Liqe, pp. 63-71 (1974)
- 1)2. Kwei. T.K.. Wang. T.T.. and Zupko. H.M.

 Diffusion in Glassy Polymers V. Combination of Fickian and Case II Mechanisms

 Macromol.. Vol. 5. pp. 645 (1972)
- 103. Lefaux. R.

 Migration of Monomers in Foods

 Ernaehrungsforschung. Vol. 16. No. 4. pp. 617-25 (1972)
- 104. Lehmann. H.D.

 Migration of Antistats in Plastics

 Chem., Phys. Chem. Anwendungstech. Grenzflaechenaktiven Stoffe. Ber.

 Int. Kongr., Vol. 6. No. 3. pp. 661-9 (1973)
- 105. Leimgruber, R.A., and Figge, K.

 Substances Migration from Plastics Food Packaging to

 Contents as a Function of the Solvent Volume to Sample
 Surface Area

 Soc. Plast. Eng. NATEC. Nov. 1977. pp. 40-43
- 136. Lewis, T.J.

 Diffusion of Isopropyl Nitrate, Acetone, and Water into Nitrocellulose
 Polymer, Vol. 19. pp. 285-290 (1978)
- 107. Machin, D. and Rogers, C.E. Concentration Dependence of Diffusion Constants in Polymers CRC crit. Rev. Macromol. Sci., Vol. 1, pp.245-313 (1972)
- 1)8. Maksimova. N.S., Sukhareva, L.V., Guricheva, Z.G., Demidova, V.M., Lazareva, N.P., and Sokolova, T.G.

 Migration of Stabilizers from Polymers Used in Medicine Ptast. Massy, No. 10, pp. 61-3 (1972)
- 139. Marketov. M.A., and Semenenko, E.I.

 Determination of Microconcentrations of Substances Migrating from Polymer Materials to Water

 Plast. Massy, No. 1, pp.57-9 (1976)
- 110. Matveeva. E.N.

 Determination of the Migration of Antioxidant on the Surface of Polymer

 Naterial

 Plast. Massy. No. 8. pp. 68-9 (1975)
- 111. Mazur. H., and Lewandowska. I.

 Study of the Migration of Benzophenone Derivative UV (Light)

 Stabilizers

 Rocz. Panstw. Zakl. Hig., Vol. 27, No. 6, pp. 611-19 (1976)
- 112. Meier, L.

 Results of Studies on the Migration of the Plasticizer from PVC into Thermoplastics

Plastverarbeiter, Vol. 28, No. 4, pp. 185-98 (1977)

- 113. Millen. W., and Hawkes. S.
 Olffusion of n-Alkanes in Poly(dimethylsiloxanes)
 Macropole, Vol. 16. No. 6. pp.1250-2 (1977)
- 114. Ministro per la Sanita. Il Modification of the Regulation 15th April. 1366. Health Regulation for Wrappings Industria Conserve. Vol. 43. No. 2, pp. 158-9 (1969)
- 115. Morano, J.
 Sorption of Vinyl Chloride in Various Poly(vinyl chloride)
 Food Simulating Solvent Systems
 Ph.D. Thesis, Rutgers Univ., 1975
- 116. Morano J.R., Giacin, J.K., and Gilbert, S.G.
 Sorption-Desorption of Vinyl Chloride in Selected PVC-Food Simultant
 Solvent Systems
 J. Food Sci., Vol. 42, pp. 230 (1977)
- 117. Morita. Z., Abul Hossain, T.N., and Iijima. T.

 Diffusion and Adsorption of a Model Cationic Dye,

 N-Nitrobenzylamine, in Polyacrylonitrile

 Bull. Chem. Soc. Jpn., Vol. 48, No. 4, pp. 1196-9 (1975)
- 118. Morsier. A. De

 Migration of Plastic Adjuvant Agents with Regard to Toxicological

 Aspects

 Ernaehrungsforschung, Vol. 16. No. 4, pp. 637-41 (1972)
- 119. Narkis, N., and Narkis, M.

 Slow Release of Water-Soluble Salts from Polymers

 J. Appl. Polym. Sci., Vol. 20, No. 12, pp. 3431-6 (1976)
- 120. Novitskaya, L.P., Kazarinova, N.F., and Kuznetsova, V.N.

 Determination of Certain Stabilizers-Antioxidants during Sanitary
 and Chemical Studies of Polymeric Materials

 Gig. Sanit., No. 7, pp. 74-7 (1977)
- 121. Ostromow, H.

 Detection of Traces of Additives in Migration from Finished High
 Polymer Products by Determining the Functional Groups of Such
 Additives

 Ann. Ist. Super. Sanita., Vol. 8, No. 2, pp. 474-89 (1972)
- 122. Pestova. A.G., Davidan. R.G., and Vladimiskaya, F.E.
 Toxicity Characterization of Polymeric Materials Used in
 the Food Industry
 Soviet Plastics. Vol. 1972. No. 3, pp. 84-6 (1972)
- 123. Peterlin. A.

 Dependence of Diffusive Transport on Morphology of Crystalline Polymers

 J. Macromol. Sci. B. Vol. 11. No. 1. pp. 57-87 (1975)
- 124. Petrova, L.I.

 Migration of Low-Nolecular-Weight Substances

 from Polystyrene Plastics into Liquid Media

- Plasto Massy, No. 12, pp. 34-5 (1976); Intl. Polyme Sci. Technol., Vol. 4, No. 5, pp. 72 (1977)
- 125. Petrova. L.I., and Boikova. Z.K.

 Study of the Health Aspects of UPM-703 H.I. Polystyrene
 Plast. Massy. No. 5, pp. 62 (1976); Intl. Polym. Sci. Technol.,

 Vol. 4. No. 1, pp. 24 (1977)
- 126. Petrova. L.I., and Ecikova. Z.K.

 Possibility of the Use of ABS Plastics in Contact with Food

 Plast. Massy. No. 12. pp. 31 (1976) Intl. Polym. Sci. Technol.,

 Vol. 4, No. 5, pp. 99 (1977)
- 127. Petrova. L.I.. Boikova. Z.K., and Guricheva, Z.G.
 Migration of Styrene from Polystyrene Plastics into Food Products
 and a Method for Determining the Monomer in them
 Plast. Massy. No. 11. pp. 57-60 (1970)
- 128. Petrova, L.I., Guricheva, Z.G., Ballova, G.D., Egorova, E.I.,

 Maksimova, N.S.; and Rudakova, M.N.,

 Toxicity Properties of High Impact Polystyrenes Based on

 Various Rubbers

 Soviet Plastics, No. 5, pp. 67-9 (1972)
- 129. Pfab. W.

 Methods for Determining Total Migration into Fatty Foods

 Ann. Ist. Super. Sanita., Vol. 8, No. 2, pp. 385-94 (1972)
- 130. Pfab, W.

 Diffusion in a Plastic-Fat System

 Dtsch. Lebensm.-Rundsch., Vol. 69, No. 4, pp. 151-62 (1973)
- 131. Pfab, w., and Muecke, G.

 Migration of Selected Monomers in Foods and Food Simulants

 Dtsch. Lebensm.-Rundsch., Vcl. 73, No. 1, pp. 1-5 (1977)
- 132. Piater. F., and Figge. K.

 Migration of Additives of Plastic Manufacturing from Films into

 Cils and Fats, and Model Systems. Comparison of Gravimetrically

 Determined Residues from Extraction Solvents with Actual

 Extracted Additives

 Dtsch. Lebensm.-Rundsch., Vol. 67, No. 8, pp. 265-9 (1971)
- 133. Piekacz. F.

 Public Health Evaluation of Polyethylene Terephthalate

 Rocz. Panst. Zakl. Hig., Vol. 25, No. 3, pp. 281-285 (1974)
- 134. Pliner, S.Kh., and Govorukhina, V.I.

 Diffusion Properties of Plastics Films in Brine
 Rybn. Khoz., Vol. 45, No. 1, pp. 70-71 (1969)
- 135. Poorten. R. Van Der Migration from Plastics Packaging Materials into Dairy Products Revue De L'Agriculture. Vol. 27. No. 6. pp. 1531-1520 (1974)
- 136. Pugina, M.I., Zalkova, G.E., Noiseev, Yu.V., Tornau, E., Kviklys, A.,
 Daumantiene, V., Jaskelevicius, B., and Maciulis, A.,
 Effect of Stabilizers and Stabilization Methods on the Properties

of Polymer Naterials. 7. Kinetic Laws of Diffusion Stabilization of Polyamides Liet. Tsr Mokslu Akado Darbo, Sero B. No. 2, pp. 69-79 (1974)

- 137. Quankenbos, H.M. Plasticizers of Vinyl Chloride Resins Migration of Plasticizer Indo Engo Chemo, Volo 46, pp. 1335 (1954)
- 138. Reed. M.C.. Klemm. H.F., and Schulz. E.F. Plasticizers of Vinyl Chloride Resins, Removal by Cil, Scapy Water and Dry Powders Indo Engo Chemo, Volo 46, pp. 1344 (1954)
- 139. Rhee, C.K., and Ferry, J.D. Diffusion of Radioactively Tagged Penetrants through Random and Block Styrene-Butadiene Copolymers and Filled cis-Polybutadiene J. Appl. Polym. Sci. Vol. 21, pp. 467-476 (1977)
- 140. Rhee. Coko. and Ferry. JoCo Diffusion of Radioactively Tagged Penetrants through Rubbery Polymers. I. Penetrants with Very Low Solubility J. Appl. Polym. Sci., Vol. 21, pp. 773-781 (1977)
- 141. Rhee. C.-K., Ferry, J.D., and Fetters, L.J. Diffusion of Radioactively Tagged Penetrants through Rubbery Polymers. II. Dependence on Molecular Length of Penetrant J. Appl. Polym. Sci., Vol. 21, No. 3, pp. 783-90 (1977)
- 142. Rienzi. Ro Determination of Migration of Vinyl Chloride Monomer out of PVC Containers for Beverages Indo Cette Bevande, Vot. 4. No. 5. pp. 110-118 (1975)
- 143. Robinson, L. Anal. Sys. for the Admission of New Additives and the Control of Ann. Ist. Super. Sanita., Vol. E. No. 2, pp. 542-9 (1972)
- 144. Rozaci. C.. Burda. J., Hlavnicka, J., Krizek, V., and Svoboda, P. Migration og Additives from Rubber Plast. Kauck, Vol. 11, No. 12, pp. 360 (1974)
- 145. Roe. R.-J. Physical Factors Controlling Retention of Additives in Polyolefins ACS, Div. Org. Coat. Plast. Chem., Prept., Vol. 34, No. 2, pp. 132-7 (1974)
- 146. Rohleder. K., and Bruchhausen, B. Von Direct Determination of Plasticizer Migration from Plastics into Fat and Fat-Containing Foods Dtsch. Lebensm.-Fundsch., Vol. 68, No. 6, pp. 180-184 (1972)
- 147. Rombusch, Ko, and Maahs, Go On the Distribution and Migration of Antistatic Agents in Specimens Made from Polyolefins and Polystyrene Angew. Makromot. Chem. (Switz.), Vol. 34, No. 531, pp. 55-73 (1973); NASA-TT-F-14794

- 148. Rost, F.E.

 Contamination of Fats with Phthalates from Plastics
 Fette, Seifen, Anstrichm., Vol. 72, No. 7, pp. 552-3 (1970)
- 149. Rubin. R.J.

 Biomedical Implications of the Migration of Phthalate Ester

 Plasticizers from PVC Plastic

 Tech. Pap., Reg. Tech. Conf., Soc. Plast., Eng., Palisades Sect.

 pp. 81-3 (March 22-22, 1973)
- 150. Rudt. U.

 Effect of Plastics on Foods
 Gordian. Vol. 71. No. 4. pp. 132-35; No. 5. pp.141-45 (1971)
- 151. Rysavy. C.

 Water Extraction of Stabilizing Additives and its Effect on

 Atmospheric Aging of Polypropylene Films

 Plasty Kauc.. Vol. 13. No. 10, pp. 297-9 (1976)
- 152. Salame. W.

 The Prediction of Liquid Permeation in Polyethylene and Related
 Polymers

 SPE Trans.. Vol. 1. No. 4. pp. 1-11 (1961)
- 153. Salame, M., and Pinsky, J.

 Permeability Prediction

 Mod. Packag., No. , pp. (1962)
- 154. Salvatore. G.

 Method of Determination of the Global Migration of Plastics and Rubben in Fatty Foods.

 Rass. Chim., Vol. 27. No. 2, pp. 57-69 (1975)
- 155. Seidler, F., Haertig, M., Woggon, H., and Uhde, N.J.

 Examinations on the Migration of (1-14C)-2-Ethyl-Hexyl Ester of

 Di-N-Octyl Tin Dithioglycolic Acid (Stabilizer Ots 15) from Hard

 PVC into Edible Cil

 Nahrung, Vol. 15. No. 2, pp. 187-90 (1971)
- 156. Seidler, H., Woggon, H., Haertig, M., and Uhde, W.J.
 Testing of Plastic Commodities: the Migration of
 His(2-Ethylhexyl) ((Di(Cctyl-1-14C) Stannylene) Dithio) Diacetate
 from Rigid Poly(Vinyl Chloride) into Edible ()il
 Nahrung, Vol. 13, No. 3, pp. 257-64 (1969)
- 157. Seidler, H., Woggon, H., and Haertig, M.,
 Testing Plastics. Study of the Migration of Di-n-Octyl (1-(14)C) Tin
 2-Ethylhexyl-Dithioglycolate from Rigid Poly(vinyl chloride) into
 Edible Cils
 Nahrung, Vol. 13, No. 3, pp. 157-64 (1969)
- 158. Semenenko, E.I., and Markelov, M.A.

 Physicochemical Basis of Sanitary Chemistry of Polymer Materials

 Khim. Farm. Zh. Vol. 10. No. 9, pp. 129-136 (1976)

 Pharm. Chem. J. (Engl. Transl.).
- 159. Sluzewska. L.

Preliminary Hygienic Evaluation of Silicones Intended for Contact with Foods

Rocz. Panst. Zakl. Hige. Vol. 21, No. 2, pp. 169-75 (1973)

- 160. Sokolowska, R.
 - Phenol Determination Methods and their Application to Hygienic Evaluation of Plastics Utility Products. IV. Migration of Phenols from Products Made from Phenol-Formaldehyde and Epoxy-Phenol Fesins Rocz. Panst. Zakl. Hig., Vol. 20. No. 4. pp. 383-89 (1969)
- 161. Sokolowska. R.

 Identification of Antioxidants Used in Polyethylene. II. Identification
 in Plastics Items and Migration Study

 Rocz. Panst. Zakl. Hig., Vol. 2J. No. 6, pp. 661-72 (1969)
- 162. Svoboca. P., Kralicek. J., Vondruskova. E., Rozaci. O., Vanek. P., and Dockal. J.

 Migration of Paraffin Waxes. I. Behavior of Paraffin 58/60 in SBR and in Natural Rubber

 Plast. Kaucuk. Vol. 13. No. 8, pp. 241 (1970)
- 163. Tarasova. N.A., Feofanov, V.D., and Gut. V.E.

 Benzene Content in Medium-Pressure Polyethylene
 Gig. Sanit., Vol. 36, No. 11, pp. 114-16 (1971)
- 164. Troparevsky. A., Pisarello De Tro, MoLo, and Mitta, AcEoAo
 Determination of Migration of Plasticizer by 14C Labeled Compounds
 Report CNEA, No. 391, pp. 11. Availo INIS Atomindex, Vol. 7, No. 5,
 Abstr. 22760 (1976)
- 165. Tsam. Z.M.

 Hygenic Evaluation of New Polymer Materials Used in Drinking

 Water System

 Hyg. Sanit... Vcl. 36. No. 7-9, pp. 453-5 (1971)
- 166. Uhde, W.J., and Woggon, H.

 Testing Plastics. 3. Migration Rate of Hydroxyphenylbenzotriazole

 Plastics into Edible Cil

 Nahrung, Vol. 12. No. 8. pp. 825-34 (1968)
- 167. Uhde, W.J., and Woggan, H.

 Analysis of Plastics Utensils. Migration of Antioxidants from Food
 Wrappings

 Otsch. Lebensm.-Rundsch., Vol. 67, No. 8, pp. 257-262 (1971)
- 168. Uhde. W.J.. and Woggon. H.

 Recent Results Concerning the Migration Behavior of Benzophenone Based

 Ultraviolet Absorbents from Polyolefins in Foods

 Nahrung. Vol. 20. No. 2. pp. 185-94 (1976)
- 169. Uhde. WeJe. Woggon, He. and Koehler. Ue

 Testing from Plastics. 2. Migration of 4.4°-Thio-bis(6-t-Butyt-m-Cresol)

 Plastics into Edible Oil

 Nahrung. Vol. 12. No. 8. pp. 813-24 (1968)
- 170. Uhde. W.J., Woggon. H.. Zydek. G., and Koehler. U.

 Testing Plastics. Migration of UV-Absorbents from Food Packaging

 Materials

Dtsch. Lebensm.-Rundsch., Vol. 65, No. 9, pp. 271-78 (1969)

171. Varsano. J.L., and Gilbert, S.G.

Evaluation of Interactions Between Polymers and Low-Molecular Weight Compounds by GLC (Gas-Liquid Chromatography). I. Methodology and Interact Evaluation

J. Pharm. Sci., Vol. 62, No. 1, pp. 87-91 (1973)

172. Vieth. W.R., and Amini. Mary A.

Generatized Dual Sorption Theory
Polym. Sci. Technol. 6, Permeability Plast. Films Coat.

Gases. Vap., Liq., pp. 48-61 (1974)

173. Vieth, W.R., Howell, J.M., and Hsieh, J.H.

Dual Sorption Theory

J. Membrane Sci., Vol. 1, pp. 17 (197)

174. Vorob'ev, V.P., Guricheva, Z.G., Petrova, L.I., and Sazhin, B.I.
Description of the Migration of Low-Molecular-Weight Components
from Polystyrene Plastics by Diffusion Equations
Plast, Massy, No. 7, pp. 57-60 (1972)

175. Wang, T.T., and Kwei, T.K.

Diffusion in Polymers

Permeability of Plastic Films and Coatings to Gases, Vapors, and Liquids, Hopfenberg, H.B., Ed.

Plenum Press, N.Y., pp. 63 (1974)

176. Westerdahl, C.A.L.

Diffusion and Persistence of Silicone Dil in Rubbers and Low Density
Polyethylene
Picatinny Arsenal Technical Report, No. 2185, March 1976

177. Westlake. J.F., and Johnson. M.
Diffusion of Stabilizers in Polymers. I.
2.4-Dihydroxybenzophenone in Polyolefins
J. Appl. Polym. Sci., Vol. 19, No. 2, pp. 319-34 (1975)

178. Wewerka. D., Fruwirth. C., and Fummel. K.

Reactions in Crosslinked Polymers. 2. Purification of
Polybutadiene by Extraction with Liquefied Butane
Kaut. Gummi. Kunstst., Vol. 27, No. 3, pp. 90-3 (1974)

179. Wharton, F.D., Jr., and Levinskas, G.J.
Toxicological Studies on Nitrile Barrier Polymers
Chem. Ind. (London), Vol. 11, pp. 470-4 (1976)

180. Wieczorek. H.

Isolation and Guantitative Determination of Organotin Compounds in
Edible Oll and Vinegar after Contact with Stabilized Rigid PVC
Films

Otsch. Lebensm.-Rundsch., Vol. 66, No. 3, pp. 92-95 (1975)

181. Wildbrett. G.
The Extracting Effect of Detergent Solutions on PVC Milk Tubes
Milchwissenschaft. Vol. 28. No. 7, pp. 443-446 (1973)

182. Wildbrett, G.

Diffusion of Phthalic Acid Esters from PVC Milk Tubing Environ. Fealth Perspect. Vol. 3. pp. 23-35 (1973)

- 183. Wilcorett. G., Evers. K. W., and Kiermeier. F.

 Investigations and Observations on the Application of Plastics
 for Foods. XII. Migration of Monomeric Plasticizers from PVC Milk
 Tubes into Cleaning Solutions
 Fette. Seifen. Anstrichm., Vol. 71, No. 4, pp. 333-335 (1909)
- 184. Wildbrett, G., Evers, K.-W., and Kiermeier, F.

 Investigations and Observations on the Application of Plastics
 for Foods, XIII. Interaction of Plastics with Milk

 Z. Lebensm.-Unters, Forsch., Vol. 142, No. 3, pp. 205-15 (1972)
- 185. Wildbrett. G., Evers. K.-W., and Kiermeier, F.

 Investigations and Observations on the Application of Plastics
 for Foods. XVI. Diffusion Process in PVC Tubing for Foods
 Werkst. Kcrros., Vol. 22. No. 9, pp. 753-759 (1971)
- 186. Wilks. R.A.. Jr.. and Gilbert. S.G.

 Sensory and Instrumental Evaluation in Model Systems of Residues

 Migrating from Can Coatings

 J. Food Sci., Vol. 37, No. 1, pp. 72-76 (1972)
- 187. Woggon, H., Jehle, D., and Uhde, W.J.

 Testing of Plastic Commodities. Migration of PVC (Poly(Vinyl Chloride)) Stabilizers into Edible Cit

 Nahrung, Vol. 13, No. 4, pp. 343-50 (1969)
- 188. Woggon. H., and Koehler, U.

 Testing of Plastic Utensils Polarographic Determination of Di-(?-EthylHexyl)-Phthalate and Investigation of the Tendency to Migration
 Kunststoffe, Vol. 57, No. 7, pp. 583-586 (1967), NASA-TT-F-13889
- 189. Woggon. H., and Koehler, U.

 Testing Plastics. 4. Migration of Plasticizers from
 Polymethacrylates into Food

 Ernaehrungsforschung. Vol. 13. No. 4. pp. 651-55 (1963)
- 190. Woggon, h., Koehler, U., and Uhde, W.-J.

 Testing Plastics. Migration of Cadmium Pigments from Food Packaging

 Materials

 Dtsch. Lebensm.-Rundsch., Vol. 64, No. 8, pp. 243-47 (1968)
- 191. Woggon: H., and Uhde, W.J.

 Antistatic Finishing of Plastics from the Food-Toxicological Point of View

 Nahrung, Vol. 21. No. 3. pp. 235-45 (1977)
- 192. Woggon, h., Uhde, W.J., and Saeuberlich, H. New Results on the Migration of Organotin Stabilizers in Food Ernaehrungsforschung, Vol. 16, No. 4, pp. 646-55 (1972)
- 193. Woggon, H., Uhde, W.J., and Zydek, G.

 Testing of Plastics, Migration of 2,6-Di-tert-Butyl-p-Cresol (8HT) in

 Edible Gils

 Z. Lebensm.-Unters. Forsch., Vol. 138, No. 3, pp. 169-77 (1968)

194. Yen. W.C.H.

Quantitative and Qualitative Study of the Migration of Organotin Stabilizer from Poly(vinyl chloride) to Liquid Foods Diss. Abstr. Int. B. Sci. Eng., Vol. 31, No. 3, pp. 1343; Order, No. 70-16963 (1970)

EUF:1627): NO CORRECTIONS APPLIED.

DUFFSEND

REVIEW AND EVALUATION OF AVAILABLE MIGRATION MODELS

Introduction

Migration of minor constituents from a polymeric film to a food or simulating solvent is controlled by both transport and thermodynamic factors. Neither can be ignored if a complete description of migration is desired. For example, the diffusion of a species (hereafter referred to as the "migrant") from a polymer film of thickness 2ℓ and volume V_p to a stirred solvent of volume V_s is given by 1

$$\frac{M_{t}}{M_{\infty}} = 1 - \sum_{n=1}^{\infty} \frac{2\alpha(1+\alpha)}{1+\alpha+\alpha^{2}q_{n}^{2}} \exp(-Dq_{n}^{2}t/\ell^{2})$$
 (1)

where the q_n's are the non-zero positive roots of

$$tan q_n + \alpha q_n = 0 (2)$$

and

$$\alpha = \left(V_{S} / V_{p} \right) K \tag{3}$$

D= migrant diffusion constant in polymer

K= C /C = equilibrium distribution coefficient

C_D = equilibrium concentration of migrant in film

C_s = equilibrium concentration of migrant in solvent

 M_{+} = amount of migrant transferred to solvent at time t

 $\rm M_{\odot}$ = amount of migrant transferred to solvent at infinite time If the initial concentration of migrant in the polymer film was $\rm C_{O}$, then $\rm M_{O}$ = $\rm V_{D}\rm C_{O}$ and

$$1 - \frac{C_{p}}{C_{0}} = \frac{M_{\infty}}{M_{0}} = \frac{\alpha}{1 + \alpha}$$

$$-33 -$$
(4)

Notice that Eq. (1) is a function of both D (a transport property) and K (a thermodynamic property). Equation (4) determins the <u>maximum</u> amount of migration that can occur and is strictly an equilibrium or thermodynamic property of the system.

Equation (1) is the complete solution for a certain class of migration problems; viz., those systems which obey Fick's two laws of diffusion and for which D and K are known. Therefore, modeling migration behavior for this type of system can be reduced to estimating, either theoretically or by semi-emperical methods, K and D.

If the polymer film is appreciably penetrated by solvent, the diffusion constant is not constant and Eq. (1) will no longer hold. But even in these systems Eq. (4), which is only a function of K, is valuable in the sense that it yields an upper limit for migration. Of course, this upper limit equals M_0 (complete extraction of the migrant) if the solvent mass is much larger than the film mass; i.e., if the film is placed in an infinite solvent reservoir, migration continues to completion at infinite time. However, in many food packaging applications (e.g. plastic bottles) α will be finite and a residual amount of migrant will be retained by the film.

In the next section, methods of theoretically estimating distribution coefficients will be discussed which will then be followed by a discussion of theoretical methods for estimating diffusion constants. A general and practical migration model will ultimately depend on how well K and D (and their temperature dependences) can be calculated from the physical properties of the polymer, solvent, and migrant.

<u>Distribution Coefficients</u>

In principle, a relatively good estimate of K should be possible for some polymer/solvent/migrant systems by using either the Flory equation of state theory of solutions $^{2-4}$ or the lattice fluid (LF) theory of Sanchez and Lacombe 5 . An important prerequisite for the application

of either theory is that the thermodynamic behavior of the migrant + polymer can be treated as an equilibrium mixture of two fluids. The amorphous component of a semi-crystalline polymer, such as polyethylene, can be treated as an equilibrium liquid if the temperature is above the polymer glass transition temperature. Under these conditions, the chemical potential of any organic migrant species (liquid or gas) within the amorphous regions can be calculated.

According to the well-known Flory-Huggins (F-H) theory of solutions⁶, the chemical potential of component 1 in a binary mixture is given by

$$(\mu_1 - \mu_1^{0})/RT = \ln \phi_1 + (1 - V_1/V_2)\phi_2 + \chi \phi_2^{2}$$
 (5)

where $\mu_1^{\ 0}$ is the molar Gibbs free energy of pure liquid component 1 at temperature T, $\phi_1=1-\phi_2$ is the volume fraction of component 1, V_1 and V_2 are the respective molar volumes of the two components and χ is the reduced residual chemical potential 4 . In the original formulation of F-H theory, χ was strictly an energetic parameter that was proportional to the energy required to form a 1-2 bond from a 1-1 and 2-2 bond. It also had a simple 1/T temperature dependence and was independent of solution composition. Now it is known that χ is in general concentration dependent and possesses a more complicated temperature dependence than 1/T. Experimentally, χ is treated as an empirical parameter which is adjusted as a function of concentration and temperature to fit experimentally determined chemical potentials.

Even in solutions containing polar components, positive χ values are usually required⁴. Large positive χ 's are, of course, thermodynamically unfavorable and will limit miscibility.

This positive character of χ has highlighted the failure of F-H theory because the sign of χ should be the same as that of the heat of mixing, ΔH_{m} . Exothermic mixing requires a negative χ , yet there exist many examples where ΔH_{m} is negative and positive $\chi^{\prime}s$ are required for the chemical potentials. Even more puzzling within the context of F-H theory is that large negative heats of mixing often occur with mixtures of non-polar components which require relatively large positive χ values (see Table I for some examples). However, both the new Flory and LF theories have resolved this apparent paradox. Experimentally, χ often has a large positive entropic component which arises, according to the Flory and LF theories, from differences in the equation of state properties of the pure components.

Formally, the concentration dependence of χ can be expressed as

$$x = x_1 + x_2 \phi_2 + x_3 \phi_2^2 + \dots$$
 (6)

There are two important limiting values of χ :

$$\chi_{1} = \chi(\phi_{1}=1) \tag{7}$$

$$\chi_{\uparrow} = \chi(\phi_{\uparrow} = 1)$$

$$\chi^{\infty} = \chi(\phi_{\uparrow} = 0) = \sum_{1}^{\infty} \chi_{i}$$
(8)

In almost all polymer solutions that have been studied, χ^{∞} > χ_{1} for the solvent chemical potential.

At equilibrium, the chemical potential (or activity) of the migrant μ_p in the amorphous regions of a semi-crystalline polymer will equal the chemical potential μ_s of the migrant in the solvent phase:

$$\mu_{\mathsf{D}} = \mu_{\mathsf{S}} \tag{9}$$

Let the migrant be component 1 and present in small quantities compared to the polymer film or simulating solvent; thus $\phi_2 \rightarrow 1$ and the migrant chemical potentials approach the following limiting forms:

$$(\mu_{p} - \mu^{0})/RT = \ln \phi_{p} + 1 + \chi_{p}^{\infty}$$
 (10)

$$(\mu_{s} - \mu^{0})/RT = \ln \phi_{s} + (1 - V_{m}/V_{s}) + \chi_{s}^{\infty}$$
 (11)

where V_m and V_s are the <u>molar</u> volumes of migrant and solvent respectively $(V_m/V_p \simeq o \text{ and is ignored})$, ϕ_s is the migrant volume fraction in the solvent phase, ϕ_p is the migrant volume fraction in the polymer phase and χ_p^∞ and χ_s^∞ are the χ^∞ values of the migrant in polymer and solvent phases, respectively. At equilibrium, Eq. (9) holds and thus the distribution coefficient is given by

$$K = \phi_s/\phi_p = \exp(V_m/V_s + \chi_p^{\infty} - \chi_s^{\infty})$$
 (12)

Equation (12) offers an alternative to extraction experiments for experimentally determining distribution coefficients. Recent advances in gas chromatographic techniques have made it possible to determine χ^{∞} in low molecular weight systems such as n-hexane/squalene⁷ and in polymer/solvent systems such as polyethylene/n-decane⁸. The necessary equations required to obtain chemical potentials from equilibrium chromatograms are discussed in references 7 and 8

and in more recent papers by Purnell⁹ and Bonner and Brookmeier¹⁰. For polymers, measurements are normally carried out above the polymer melting point or glass transition temperature. These temperatures will usually be well above the anticipated use temperatures of the polymeric food packaging material. However, with the aid of theory, experimental χ^{∞} values can be extrapolated accurately to lower temperatures.

The Flory²⁻⁴ and lattice fluid⁵ (LF) theories incorporate the "equation of state" properties of the pure component fluids. Both theories require 3 equation of state parameters for each pure component which are determined from PVT data. For the LF, about 60 low molecular weight fluids⁵ and 10 different polymers¹¹ have already been so characterized. For a binary mixture, LF theory requires 7 parameters: 3 for each pure component, which are already known or are calculable from PVT data, and a seventh parameter that characterizes the interaction between the two components. The Flory theory requires an eighth parameter that is related to the surface/volume properties of the pure components. A relatively concise review and comparison of these two theories has been given by Sanchez¹².

For the LF, χ^{∞} for component 1, the migrant, is given by $\chi^{\infty} = \frac{M_1}{v_1^{\gamma} \rho_1} \left[\hat{\rho}_2^{\gamma} X_1 + (\hat{\rho}_1^{\gamma} - \hat{\rho}_2^{\gamma}) \hat{T}_1 + (\hat{v}_2^{\gamma} - 1) \ln(1 - \hat{\rho}_2^{\gamma}) - (\hat{v}_1^{\gamma} - 1) \ln(1 - \hat{\rho}_1^{\gamma}) + \ln(\hat{\rho}_2^{\gamma} / \hat{\rho}_1^{\gamma}) \right]$ where

 $\begin{array}{l} \text{M}_1\text{= molecular weight of component 1 (migrant)} \\ \text{T}_1^{\star}, \ v_1^{\star}, \ \rho_1^{\star}\text{= characteristic temperature, volume, and mass} \\ & \text{density, respectively, of the migrant} \end{array}$

 $\tilde{\rho}_1 = \rho_1/\rho_1^* = 1/\tilde{v}_1$ reduced migrant density $\tilde{\rho}_2 = \rho_2/\rho_2^* = 1/\tilde{v}_2$ reduced polymer density or reduced simulating solvent density $\tilde{T}_1 = T/T_1^*$ reduced migrant temperature

$$X_1 = \Delta P^* v_1^* / RT \tag{14}$$

and ΔP^* represents the net change in cohesive energy density upon mixing components 1 and 2 at the absolute zero of temperature. X_1 is the only unknown parameter in Eq. (13). All others are known or derivable from pure component PVT data. An experimental value of χ^∞ would establish the value of X_1 , of course, but other kinds of solution data (often more accessible experimentally) such as heats of mixing, critical temperatures, solution densities, etc. can be used to determine X_1 . Thus, LF theory offers a method of calculating χ^∞ values without actually measuring chemical potentials directly. To illustrate this possibility, χ^∞ values have been calculated for some polyisobutylene solutions using ΔH_m data to fix X_1 . As a polymer solution becomes dilute in polymer (component 2), the heat of mixing approaches a limiting value, $\Delta H_m(\infty)$, defined by:

$$\Delta H_{m}(\infty) = \lim_{\phi_{2} \to 0} \Delta H_{m}/\phi_{2}$$
(15)

In Table I $\Delta H_m(\infty)$ values at 298 K for polyisobutylene in n-pentane, n-octane, cyclohexane, and benzene are tabulated. A striking feature of the data is that 3 out of 4 of these non-polar solutions are exothermic. Notice, however, that all

of the calculated ΔP^* and X_1 values are positive as one might expect for these non-polar components. The calculated X_1 values have then been used in Eq. (13) to calculate χ^{∞} ; the experimental χ^{∞} values are also tabulated in Table I for comparison. Also listed are the experimental and theoretical values of $X_1 = \chi$ (ϕ =1) which shows how χ can vary with concentration. Although the agreement is not spectacular, it is encouraging. Similar results can be obtained with the Flory theory whereas the Flory-Huggins theory would fail miserably.

data references		13, 14	13, 15	13, 16	13, 17
calc.		92.0	0.43	0.34	0.63
χ _η expt. c αlc.		0.49	0.46	0.47	0.50
χ^{∞} expt. calc.		69.0	0.38	0.36	0.73
x expt.		0.93	0.5	0.50	1.15
* Δp (MJ/m³)		10.4	6.04	4.91	20.07
x ₁ ×10 ²		4.980	2.128	2.442	8.180
ΔH _m (∞) (J/mol)		-201	-159	- 38	+1090
	-41-	n-pentane	n-octane	cyclohexane	benzene

Table I A comparison of experimental and theoretical reduced residual chemical potentials for polyisobutylene solutions at 298K.

1. General Properties

Typically, the self-diffusion constant D of an organic liquid is about 10^{-9} m²/sec. At low concentrations in a polymer, the same organic species diffuses at a drastically reduced rate; D can vary from about 10^{-13} m²/sec at T_g + 100 K to about 10^{-20} m²/sec near T_g.

Most diffusion studies have taken the form of permeation or sorption experiments performed on amorphous polymers (lightly crosslinked) above their glass transition temperatures. Whereas diffusion behavior is relatively simple at temperatures above T_g , it is exceedingly complex at temperatures near or below T_g .

In the usual absorption experiment a polymer film, initially free of diffusant molecules, is suddenly exposed to an organic vapor at a fixed pressure and the gain in weight of the film is monitored as a function of time. Desorption of the diffusant can also be studied by reducing the pressure to a new fixed value and following the film weight loss. Data from a sorption experiment (either absorption or desorption) are generally represented by plotting the amount of vapor M_t absorbed or desorbed against the square root of time. At long times equilibrium is approached and $\mathsf{M}_\mathsf{t}\!\!\to\!\!\mathsf{M}_{\scriptscriptstyle \square}$.

Crank discusses at length the method of data analysis required to obtain diffusion constants from sorption data. It is assumed that D(c) is a function of concentration c, but not of time, and that the diffusant concentrations at

the film surface increase or decrease instantaneously with pressure to their equilibrium values. Under these conditions the sorption is called Fickian and sorption curves are expected to possess the following properties:

- a) Sorption curves are initially linear in $t^{1/2}$. For absorption, the linear region extends to over 60% of M_{∞} . For desorption, linearity is obtained almost up to equilibrium if, as would normally be expected, dD/dc > 0.
- b) Above the linear portions, both absorption and desorption are concave to the $t^{1/2}$ axis, irrespective of the form of D(c).
- c) Sorption curves are superimposable. A series of absorption curves for films of different thicknesses (ℓ) are superposable if M_t is plotted against $t^{1/2}/\ell$. The same applies to a corresponding series of desorption curves.

These properties are independent of the form of D(c) and provide an experimental means of determining whether a given system exhibits Fickian sorption. One of the most important findings of sorption studies is that at temperatures well above T_g , the sorption kinetics of organic vapors are invariably Fickian.

Temperature dependent sorption studies have also revealed another characteristic property of small molecule diffusion in polymers: the temperature dependence is strong and non-Arrhenius. A plot of log D vs 1/T will usually be non-linear. For example, Hayes and Park 18 studied sorption of benzene in natural rubber and found that the apparent activation energy, $\Delta E^* \equiv -R \ dlnD/d(1/T)$, is about 29kJ/mole at 373 K but increases to 96kJ/mol at 273 K.

Another feature of the temperature dependence, which is especially relevant for migration studies, is the finding that ΔE^* often appears to be independent of the diffusant's chain length or branching. Such has been the case for isomeric hydrocarbons in natural rubber 19 and polyisobutylene 20 and n-alkyl acetates in polymethyl acrylate 21,22 . In the case of natural rubber, the constancy of ΔE^* has been shown to hold up to as large a molecule as octadecane 23 . These findings tend to support the thesis that the temperature dependence of diffusion is largely determined by the properties of the polymer and is relatively independent of the size and shape of the diffusant.

2. Diffusion above T_g

Theories of the diffusion constant fall into two broad classes: In one, which is especially relevant for migration studies, attention is directed at how the magnitude of D and its temperature dependence are affected by such factors as the size and shape of the diffusant, the nature of the polymer, and the intermolecular interaction between diffusant and polymer. In the second class, interest is focused on interpreting the concentration and temperature dependence of D and not its magnitude. A 1973 review of the latter class of theories is available 24 while the former and more important class was reviewed in 1968 by Kumins and Kwei 25.

Of the theories reviewed in 1968, two stand out. These are the free volume theories of Cohen and $\text{Turnbull}^{26,27}$ and Bueche^{28} . Both theories require the probability $\text{P(v}^*)$ that the local volume v associated with the molecule or a "segment" of the molecule be greater than some critical volume v*. The theories are different in that different

methods are used for calculating $P(v^*)$. Cohen and Turnbull assumed that a multinomial distribution of free volumes exist in a liquid to derive:

$$P(v^*) = \exp(\gamma v^* / v_0 f)$$

$$D \sim \bar{u} P(v^*)$$
(16)

where f is the fractional free volume, v_0 is the molecular or segment volume when f=0, γ is a dimensionless constant (1/2 < γ <1), and \bar{u} is the average molecular or segment velocity $[\bar{u}=(kT/M)^{1/2}]$. Beuche used the thermodynamic theory of fluctuations, orginally derived by Einstein, to obtain

$$P(v^*) = \frac{1}{2} \operatorname{erfc} \left[\frac{v^* - \langle v \rangle}{(2\beta \langle v \rangle kT)^{1/2}} \right]$$

$$D \sim P(v^*)$$
(17)

where $\langle v \rangle$ is the average segment volume, β is the isothermal compressibility of the polymer and erfc is the complementary error function.

Although both of these theories in their original formulations did not consider the diffusion a small molecule in a polymer, they have been successfully applied to such systems. Fujita²⁹ has demonstrated that the Cohen-Turnbull theory adequately describes the temperature dependence of diffusion in polymers in several systems. (Acutally Fujita used an empirical equation for D due to Doolittle³⁰ which is equivalent to the Cohen-Turnbull equation for D). Fujita²⁹ and others³¹⁻³³ have shown that the Cohen-Turnbull theory, properly modified, adequately accounts for the concentration dependence of D up to 10% of diffusant. Kumins and Roteman³⁴ have used Bueche's theory successfully to correlate the diffusion behavior of small gas molecules with their van der Waal volumes.

However, the success of both theories must be viewed as being primarily correlative rather than truly predictive.

Recently Sanchez 35 obtained the following expression for the diffusion of a small molecule in a polymer:

$$D_{o} = D(c=o) = \frac{\bar{u}}{6} (v^{*})^{1/3} \operatorname{erfc} \left[\frac{v^{*} - \bar{v}^{\infty}}{(2\beta \bar{v}^{\infty} k)^{1/2}} \right]$$
 (19)

where \bar{v}^{∞} is the <u>partial molar volume</u> of the diffusant in the limit of zero concentration, β is the compressibility of the polymer, and all other symbols have the same meaning as before. Equation (19) can also be suitably modified to treat the diffusion of a large molecule composed of N segments, each of which is able to execute independent diffusive motions.

Although Eq. (19) has yet to be tested quantitatively, it has the potential of being a predictive theory of diffusion. It is predictive in the sense that all of the requisite parameters and variables can be determined independently from other physical data; v^* can be determined from viscosity or self-diffusion data on the pure liquid diffusant; \bar{v}^{∞} can be semi-quantitatively calculated using either the Flory $^{2-4}$ or lattice fluid 5 theory of solutions; and β can be determined either experimentally or theoretically.

The attractive property of Eq. (19) is that it embodies all of the physical factors judged important for diffusion in polymers through v^* , \bar{v}^∞ , and β ; v^* is a unique property of the shape and size of the diffusant; \bar{v}^∞ is a property which depends sensitively on the polymer-diffusant intermolecular

interaction; and β , of course, is a characteristic property of the polymer.

Qualitatively, Eq. (19) also explains why the diffusion of a small molecule decreases by 4 or 5 orders of magnitude in a polymer. This can best be illustrated by expanding erfc X in an asymptotic series 36 so that Eq. (19) becomes (valid for large X):

$$D_{o} \approx \frac{\bar{u}}{6} \frac{\left(2\beta \bar{v}^{\infty} kT/\pi\right)^{1/2}}{v^{*} - \bar{v}^{\infty}} \left(v^{*}\right)^{1/3} \exp \left[-\frac{\left(v^{*} - \bar{v}^{\infty}\right)^{2}}{2\beta \bar{v}^{\infty} kT}\right]$$
(20)

The equation for the self-diffusion constant D_d of the diffusant will be the same as Eq. (19) or (20) except that \bar{v}^{∞} is replaced by the molar volume v_d of the diffusant and β is replaced by the compressibility β_d of the diffusant. Compressibilities of polymer liquids are just about one order of magnitude smaller than those of similar low molecular weight liquids. Thus, the big difference between D_d and D_o is the compressibility of the medium in which the diffusant molecule finds itself. (Volume fluctuations are directly proportional to β). Decreasing β by an order of magnitude can diminish D by a substantially larger amount since β appears in the exponential.

3. Diffusion below T_q

Analysis of migration or diffusion in polymers is often based on ideal conditions. That is, the diffusion constant is assumed to be constant independent of the concentration of the diffusing material in the polymer and the concentration in the polymer is assumed to be given by Henry's Law

$$C = kp$$
 (21)

at equilibrium, where p is the pressure of the diffusant in the gas surrounding the polymer or the concentration of the diffusant in a solution surrounding the polymer. However for some polymeric systems, especially glassy polymers, these conditions do not hold, so that a more complicated analysis is required.

Vieth 37 and others have studied diffusion and sorption in systems in which Eq. 21 is not obeyed. An example of such a system is methane in orientated polystyrene. The slope of the solubility versus pressure is not constant as in Eq. 21, but decreases with pressure and becomes constant at high pressures. Vieth and coworkers postulated that two modes of sorption are operative in such systems. The first mode of sorption, C_D , is proportional to the pressure, while the second mode of sorption, C_H , obeys Langmir sorption. Thus at equilibrium,

$$C = C_D + C_H = k_D p = \frac{C'_H b p}{1 + b p}$$
 (22)

The second mode of sorption, C_H , is considered to be due to holes or voids in the polymer. Methods have been given 37 to determine the constants k_D , b and C_H^{-1} in Eq. 22 from sorption curves. It was demonstrated that the equilibrium gas solubilities in glassy polymers may be characterized by the dual sorption model mathematically expressed by Eq. 22.

Vieth and Sladek 38 developed a theory of diffusion in systems that have dual sorption. They assumed the concentration in the Langmuir isotherm, C_H , of the adsorption did not contribute to diffusion and that the diffusion constant D of C_D , the Henry's law isotherm , is independent of concentration. They obtained the diffusion equation

$$D \frac{\partial^{2} C_{D}}{\partial \chi^{2}} = \frac{\partial^{2} C_{D}}{\partial t} \left[1 + \frac{C'_{H} b/k_{D}}{(1+bC_{D}/k_{d})} 2 \right]$$
(23)

and applied Eq.23 to transient sorption of CO2 in Mylar. Eq. 23 could not be analytically solved for the boundary conditions of transient sorption because it is not linear in C_D . Therefore, numerical solutions of Eq. 23 were obtained for assumed values of b, C_H ' and k_p . A method was given for matching these theoretical curves to the experimental sorption curves to obtain the diffusion constant D. Good agreement with the observed absorption was obtained. The method has since been applied to other systems exhibiting dual sorption.

Paul and Kemp³⁹ have investigated time lag experiments for systems exhibiting dual sorption. While Eq. 23 cannot be solved analytically for the boundary conditions (Barrer conditions) used for time lag experiments, analytic expressions for the permeability and time lags were derived. Kemp⁴⁰ made time lag experiments on a membrane of a silicone rubber impregnated with molecular sieve particles. Becasue the molecular sieve particles exhibited large Langmuir adsorption of the gases used, the membrane exhibited dual sorption.

He was able to determine the constants b, C_H , k_D and D from measurements of the silicone rubber and molecular sieves and predict the results of the time lag experiments. Good agreement was obtained.

The time lag experiment may be used to determine if a material obeys ideal diffusion. Fig. 1 shows the amount of ${\rm CO_2}$ (AQ $_{
m t}$) diffused through a membrane versus the time. At times greater than 100 minutes, the amount increases linearly with time with a slope, transmission coefficient, of P = 0.1564 cc/min. Extrapolating this linear relationship (dashed curve) to $AQ_t = 0$ gives a time lag of 81 minutes. The amount of ${\rm CO}_2$ versus time that would diffuse through the membrane for ideal diffusion with these values of the transmission coefficient and time lag has been computed and is shown by the crosses. This curve is far from the experimental curve indicating that diffusion of ${\rm CO}_2$ in this membrane is not ideal. In fact, the membrane is one made by Kemp to have strong dual sorption. Thus, examination of the time lag curve of a membrane may be used to determine if the system shows ideal diffusion.

A simple test of ideal diffusion from a time lag experiment may be made as follows. Determine the transmission coefficient T and time lag θ for the system. Then for ideal diffusion, the amount of gas that has diffused through the membrane at a time equal to the time lag θ is given by 0.3343 θ T.

If the amount of gas at the time lag differs from this value, the system does not exhibit ideal diffusion. For the case discussed, we obtain 0.3343 \times 81 \times 0.1564 = 3 cc. Since the experiment gives 1 cc, the system does not obey ideal diffusion.




Figure 1. Amount of CO_ diffused through a silicone rubber to brane impregnated with molecular sieve particles.

G. AISCELLANEOUS

N,N'-Diphenyl thiourea (thiocarbanilide)	0.5/P VC (c)
Cyanoguanidine (Dicyandiamide)	1/P01
$N-n-A1ky1-N'-carboxymethy1-N,N'-trimethylenedigly$ $R = C_{14}^{-C}18$	cine 1.35/NR
ho-t-Amylphenol- Formaldehyde Resins	2.1/PA
Nylon 66/610/6 terpolymer	1.5/PO4
Poly(1,4-cyclohexylenedimethylene-3,3'- thiodipropionate) partially terminated with	0.5/PP/ 005

D. PHENOLS (continued)

Tetra-:

Tetrakis[methylene(3,5-di-t-butyl-4-hydroxy-bydrocinnamate)] methane Irganox 1010

.5/PO .05/E-MA, E-AA/ .005 .5/PS,E-AA,E-VAC, S-B,IB 1/POM .5/POM

E. PHOSPHITES

Hydrogenated 4,4'-i-propylidene diphenol-phosphiteester resins 2400-3000

0.55/P VC (c)

4,4'-i-Propylidenediphenol alkyl (C_{12} - C_{15})-phosphites

1/P VC (c)

Tri(mixed mono- and dinonyl phenol) phosphite

2-t-Butyl- α -(3-t-Butyl-4-hydroxyphenyl)- ρ -cumenyl bis(p-nonylphenyl)phosphite

1.35/NR, B-A, A-B-S, B-S/.004

Cyclic neopentanetetrayl bis(octadecyl phosphite)

0.25/P0 0.15/P0 0.20/PS,PS

F. THIO CARBOXYLIC ACIDS AND ESTERS

Thiodipropionic Acid

Dimyristyl thiodipropionate

Dicetyl thiodipropionate

Distearyl thiodipropionate Antioxydans AS Advastab PS 802

References

- 1) J. Crank, "Mathematics of Diffusion", 2nd Ed. Clarendon Press, Oxford (1975).
- 2) P. J. Flory, <u>J. Amer. Chem. Soc.</u>, <u>87</u>, 1873 (1965).
- 3) B. E. Eichinger and P. J. Flory, Trans. Faraday Soc., 64, 2035 (1968).
- 4) P. J. Flory, <u>Discuss. Faraday Soc.</u>, <u>49</u>, 7 (1970).
- 5) I. C. Sanchez and R. H. Locombe, J. Phys. Chem, 80, 2352, 2568 (1976).
- 6) P. J. Flory, "Principles of Polymer Chemistry", Cornell Univ. Press, Ithaca, NY (1953).
- 7) J. R. Conder and J. H. Purnell, <u>Trans. Faraday Soc.</u>, <u>65</u>, 839 (1969).
- 8) N. F. Brockmeier, R. W. McCoy and J. A. Meyer, Macromolecules. 5, 130 (1972).
- 9) H. Purnell, "Advances in Analytical Chemistry and Instrumentation", Vol. 2, John Wiley & Sons, New York (1973).
- 10) D. C. Bonner and N. F. Brookmeier, Ind. Eng. Chem., Process Des. Dev. 16, 180 (1977).
- 11) I. C. Sanchez and R. H. Lacombe, J. Poly. Sci. Polym. Letters Ed., 15, 71 (1977)
- 12) I. C. Sanchez, "Polymer Blends", edited by D. R. Paul and S. Neuman, Vol. 1, Academic Press, New York (1978).
- 13) G. Delmar, D. Patterson, and T. Somcynsky, J. Polym. Sci, 57, 79 (1962).
- 14) B. E. Eichinger and P. J. Flory, Trans. Faraday Soc., <u>64</u>, 2061 (1968).
- 15) P. J. Flory, J. L. Ellenson and B. E. Eichinger, Macromolecules, 1, 279 (1968).
- 16) B. E. Eichinger and P. J. Flory, <u>Trans. Faraday Soc.</u>, <u>64</u>, 2061 (1968).
- 17) B. E. Eichinger and P. J. Flory, <u>Ibid.</u>, <u>64</u>, 2053 (1968).
- 18) M. J. Hayes and G. S. Park, <u>Ibid</u>, <u>51</u>, 1134 (1955).
- 19) A. Aitken and R. M. Barrer, <u>Ibid</u>, <u>51</u>, 116 (1955).
- 20) S. Prager, E. Bagley and F. A. Long, J. Amer. Chem. Soc., 75, 1255 (1953).
- 21) H. Fujita, A. Kishimoto, and K. Matsumoto, Trans. Faraday Soc. 56, 424 (1960).
- 22) H. Fujita, "Diffusion in Polymers", ed. by J. Crank and G. S. Park, Academic Press, NY (196
- 23) I. Auerback, et. al., J. Polym. Sci., 28 129 (1958).
- 24) R. K. Ghai, H. Ertl, and F. A. L. Dullien, <u>AICHE Journal</u>, <u>19</u>, 881, 1215 (1973).
- 25) Chapter 4 in reference 22
- 26) M. H. Cohen and D. Turnbull, <u>J. Chem. Phys.</u>, <u>31</u>, 1164 (1959).

- 27) D. Turnbull and M. H. Cohen, <u>Ibid</u>, <u>52</u>, 3038 (1970).
- 28) F. Bueche, Ibid, 21, 1850 (1953).
- 29) H. Fujita, Fortschi. Hochpolym. Forsch., 3, 1 (1961).
- 30) A. K. Doolittle, J. Appl. Phys., 22, 1471 (1951), 23 236 (1952).
- 31) A. Kishimoto and Y. Endu, J. Polym. Sci. A.;, 1799 (1963).
- 32) A. Kishimoto, Ibid, 2, 1421 (1964).
- 33) A. C. Newns, Trans. Faraday Soc. 59, 2150 (1963).
- 34) C. A. Kumins and J. Poteman, <u>J. Polym. Sci.</u>, <u>55</u>, 699 (1961).
- 35) Unpublished calculations of I. C. Sanchez.
- 36) "Handbook of Mathematical Functions", M. Abramowitz and I. A. Stegun editors, Dover Publications, New York (1965) p. 298.
- 37) W. R. Vieth, J. M. Howell and J. H. Hsieh <u>J. Membrane Sci.</u>, <u>1</u>, 177 (1976) and references given therin.
- 38) W. R. Vieth and K. J. Slakek, J. Coll. Sci, 20, 1014 (1965).
- D. R. Kemp and D. R. Paul J. Polm. Sci., Part A-2, 12, 485 (1974).
 D. R. Paul and D. R. Kemp J. Polm. Sci, Part C, 41, 79 (1973).
- Dissentation, the University of Texas, (1972).

 University Microfilms Ann Arbor, Mich. No. 73-466.

PRELIMINARY CLASSIFICATION OF ADDITIVE TYPES Introduction

A list of FDA approved additives (Section 178) for plastics to be used in contact with food are classified as to their chemical characteristics, along with their maximum allowable amounts (%)/in particular types of plastics/and the maximum thickness of the plastics in inches.

Classification

A. ALCOHOLS AND ESTERS

1,3 - Butanediol

Pantaerythritol 0.4/PVC
Pantearythritol stearate 0.4/PVC

B. BENZOPHENONES

Advastab 46
Cyasorb UV531

2-Hydroxy-4-i-octoxy-benzophenone
Methanone
[2-Hydroxy-4-(i-octoxy)pheny1]pheny1

0.5/PO

2-Hydroxy-4-n-octoxy-benzophenone

C. METALLIC SALTS

1.	CALCIUM:	benzoate	
		myristate	
		ricinoleate	1/POM(c)
		stearate	
2.	COPPER:	cupric acetate	.025/NY66/.0012
		cupric carbonate	.005/NY66/.0015
		cuprous bromide	.0175/NY66/.0015
		cuprous iodide	.0025/NY66/.0015
3.	LITHIUM:	iodide	.065/NY66/.0012
4.	MAGNESIUM:	salicylate	0.3/RPVC(c)
5.	POTASSIUM:	bromide	0.18/NY66/.0015

PVC 6. TIN: Di-n-octyl-tin maleate polymer Di-n-octyl-tin-bis(i-Octylmercaptoacetate) PVC Poly ((1,3-di-buty1-di-Stannthianediylidene)1,3-dithio] 0.2/PVC 7. ZINC: dibutyldithiocarbamate 0.2/IB-IP(c)0.3/RPVC salicylate palmitate stearate PHENOLS Mono-: 2,6-Di-t-butyl-p-cresolIonol BHT Advastab 401

0.1/E-P(c)/.0025 .025 2,6-Di-t-butyl-4-ethyl-phenol Antioxidant 724

2,6-Bis(1-methylheptadecyl)-p-cresol .3/P0/.004

4-Hydroxy methyl-2, 6-di-t-butyl phenol Antioxidant 754

D.

n-Octadecyl- β -(4'-hydroxy-3'5'-di-t-butyl phenyl) .25/PO/.0025 propionate .05/PO/no limit

Octadecyl-3,5-di-t-butyl-4-hydroxy-hydrocinnamate .25/PS,PS Irganox 1076 .5/A-B-S

2(2'-Hydroxy-5'-methyl phenyl)benzotriazole .25/PVC(c), PS Tinuvin P

2(3'-t-Buty1-2'-hydroxy-5'-methy1pheny1)-5-.5/PO chlorobenzotriazole Tinuvin 326

.5/PS,PO Butyrated styrenated cresols

D. PHENOLS (continued)

Di-:


```
4,4'-Methylene-bis (2,6-di-t-butylphenol)
                                                 .25/PHC resins,
          Antioxidant 702
                                                    turpene resins
                                                  .5/PE,PB
   2.2'-Methylene-bis(6-t-butyl-4-ethylphenol) .6/A-B-S
                                                  .1PA
   2,2'-Methylene-bis(4-methyl-6-t-butylphenol) .1/PO
                                                   1/POM(c)
                                                   .5/POM
   4,4^{\circ}-Butylidene-bis(4-t-butyl-m-cresol)
                                                   .5/PP
                                                   .3/PE
   4,4'-Thio-bis (6-t-butyl-m-cresol)
                                                   .25/PE
      Santonox
      Advastab 415
      Antioxydans KS
   2,2'-Methylene-bis[6-(1-methylcyclohexyl)-p-cresol] .2/PE/.0005
   4,4'-Cyclohexylidene-bis(2-cyclohexylphenol)
                                                          .1/PO
   2,2'-Methylene-bis(4-methyl-6-nonylphenol)
                                                         A-B-S
Tri-:
   2,6-Bis(2-hydroxy-3-nony1-5-methy1-benzy1)-p-cresol A-B-S
   Tris (2-\text{methyl}-4-\text{hydroxy}-5-t-\text{butylphenyl}) but ane
                                                           .25/A-B-S
                                                           1/A-B-S
                                                           .2/PS
   1,3,5-Trimethy1-2,4,6-tris-
                                                           . 5
      (3,5-di-t-butyl-4-hydroxybenzyl)benzene
                                                           1/NY
      Ionox 330, Antioxidant 330
   1, 5, 5-Tris (3, 5-di-t-buty1-4-hydroxy-hydro-
                                                           .25/PP
      cinnamoy1) hexahydro-s-triazine
                                                           .1/PE
                                                           .5/E-P-EN/
                                                              .005/.005
   1, 3, 5-Tris(3, 5-di-t-buty1-4-hydrobenzy1)-
                                                           .25/PP
      5-triazine-2,4,6(1H,3H,5H)trione
                                                           .1/PE
                                                           .5/PE
```

.5/E-P-EN/


ABBREVIATIONS FOR POLYMERS

- AA Acrylic Acid
- A Acrylonitrile
- B Butadiene
- (C) Copolymer
- E Ethylene
- EN 5-Ethylidine-2-norbornene
- IB Isobutylene
- IP Isoprene
- 1A Methacrylic Acid
- NR Natural rubber
- NY Nylon
- P Propylene
- PA Polyamide
- PBD Polybutadiene
- PE Polyethylene
- PHC Petroleum hydrocarbon
- PO Polyolefin
- POM Polyoxymethylene
- PP Polypropylene
- PVC Poly(vinyl chloride)
- S Styrene
- VAc Vinyl acetate

Molecular Models of Some of the Additives (0.1nm or 1Å is represented by 1.2 cm of the model)










n-Octadecyl 3,5-di-t-butyl-4-hydroxyhydrocinnamate 2,6-Di-t-butyl-p-cresol







Tetrakis [methylene (3,5-di-t-butyl-4-hydroxyhydrocinnamate)] methane







U.S. DEPT. OF COMM. BIBLIOGRAPHIC DATA SHEET 1. PUBLICATION OR REPORT NO. NO. 2. Gov't	Accession 3. Recipient's	Accession No.		
4. TITLE AND SUBTITLE	5. Publication	Date		
AN EVALUATION OF EXISTING MODELS DESCRIBING THE				
MIGRATION OF ADDITIVES IN POLYMERS	6. Performing	Organization Code		
7. AUTHOR(S) 1. C. Sanchez; S. S. Chang; F. L. McCrackin; & L. E. Sn	nith 8. Performing	Organ. Report No.		
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. Project/Ta 5630446	ask/Work Unit No.		
NATIONAL BUREAU OF STANDARDS DEPARTMENT OF COMMERCE WASHINGTON, D.C. 20234	11. Contract/C	Grant No.		
12. Sponsoring Organization Name and Complete Address (Street, City, State, ZIP)	13. Type of Re	eport & Period		
	Covered			
	Final 9-1-	77 to 3-30-78		
same as Item 9	14. Sponsoring	3 Agency Code		
15. SUPPLEMENTARY NOTES				
16. ABSTRACT (A 200-word or less factual summary of most significant information	on. If document includes a si	gnificant		
bibliography or literature survey, mention it here.)				
The objective of this work is the develop	ment of mathematical	models		
that describe the migration of a variety of small				
that have applications in food contact uses.				
these models will be able to predict the amount				
given any particular time and temperature histo				
serve as the technical basis for more efficient				
existing frameworks or in the design and implem	mentation of new ind	lirect		
additive regulations or policy.				
The first steps in the development and ass	sessment of such mod	lals		
are given in this report. The first section presents a preliminary survey				
of migration data applicable to food contact situations that are available				
in the current literature. The second section				
describing migration and evaluates their present and potential utility.				
17. KEY WORDS (six to twelve entries; alphabetical order; capitalize only the first name; separated by semicolons)	t letter of the first key word u	nless a proper		
Additives; diffusion; food additives; indirect addit regulation	ives; migration; mo	dels;		
18. AVAILABILITY	19. SECURITY CLASS (THIS REPORT)	21. NO. OF PAGES		
For Official Distribution, Do Not Polosson NTIC				
For Official Distribution. Do Not Release to NTIS	UNCL ASSIFIED	70		
Order From Sup. of Doc., U.S. Government Printing Office	20. SECURITY CLASS	22. Price		
Washington, D.C. 20402, SD Cat. No. C13	(THIS PAGE)	¢5 05		
X Order From National Technical Information Service (NTIS) Springfield, Virginia 22151	UNCLASSIFIED	\$5.25		





6-
E -
-